READING A SKETCH BY HUNCH

by

James Richard Taggart

Submitted in Partial Fulfillment of the Requirements

for the Degree of

Master of Science

at the

Massachusetts Institute of Technology

May, 1973

Signature of Author_____
Department of Electrical Engineering, May 11, 1973

Certified by_____
Thesis Supervisor (Academic)

Accepted by_____
Chairman, Departmental Committee on Graduate Students

READING A SKETCH BY HUNCH

by

James Richard Taggart

Submitted to the Department of Electrical Engineering on May 11, 1973 in partial fulfillment of the requirements for the Degree of Master of Science.

ABSTRACT

This thesis describes the development of a computer system, HUNCH, intended to provide a simple means for a person to communicate with a computer his ideas through the medium of sketching. The emphasis is not on developing a computer system which produces finished quality drawings from sketched input, but rather on having the computer understand what is meant by the sketch. An overview of the intended goals of such a system is described, along with a comparison to other systems of sketch recognition. A history of the development of HUNCH is given to show the reader the evolution of the ideas invoked by HUNCH as it currently stands. A description of how HUNCH performs a data reduction pass to simplify and structure the sketch is given. Finally, a proposal for a graphical compiler is made to permit development of a system which would be able to understand sketches of a predefined class.

Thesis Supervisor: Nicholas P. Negroponte
Title: Associate Professor of Architecture

ACKNOWLEDGEMENTS

It is traditional to thank everybody in the world in this section. Special reference must be made to Nick Negroponte for providing the inspiration, and to the NSF and Project MAC for providing the means for keeping body and soul together while the project was carried out. There are also nameless millions who have contributed over the years to the development of HUNCH, especially Doris Ju and Cindy O'Connell who had to work under my direction, and Mike Miller and Chris Herot, who have been bricks throughout. Leon Groisser should be thanked for providing a needed boot at a crucial moment. Finally, a nod to Archie the Architect, for whom this system has been developed.

TABLE OF CONTENTS

ORGANIZATION

The body of this paper is divided into four parts: overview, past, present, and future. The first part of the paper is a look at the goals for developing an interactive sketching system. Other implimentations of computer systems are described, and how they matched up to the defined goals is discussed. The second part is a history of events from its inception to HUNCH in its present state. Such a description seems important for two reasons. First, while the way HUNCH works can be understood without the history attached, why HUNCH exists as it is, and the motivation for the fourth part of the paper needs as part of its explanation how the ideas were derived and which ideas were discarded. HUNCH in its present form appears to be a regression from earlier successes. The motivation for this change of state is best explained by describing the sequence of events which led to the current state. Second, some of what has been learned about sketch recognition through the development of HUNCH is represented only by certain elements which are NOT included, perhaps despite earlier versions with these features. The knowledge gained by failures and changes of attitude over time is almost as great as that which currently is known. This history of HUNCH, then, is an attempt to apprise the reader of this knowledge.

The third part of the paper is a description of how the system as it currently exists is run. An extensive description of how

straight line data is extracted from the raw sketched input is included. This description not only shows how the more complicated portions of HUNCH work, but also indicates the philosophy of how operations are performed in a HUNCH-like way. From this outlook, one can see how other functions, which might be added to the HUNCH system later, would be implemented.

The last section of the paper may be looked on as conclusions and indications for future work. As it exists now, HUNCH falls short of its stated goals by quite a distance. Its biggest shortcoming is in its inability to derive a higher level description from a sketch. The last section provides the frame of mind which one might need in order to begin solving this inability. The solution proposed is neither complete nor rigorous, and in that sense, it seems strangely inconclusive. The only explanation I can offer is that the solution proposed seems to solve all the challenges I can think of, although sometimes the thinking required seems unnecessarily baroque. There must be simpler solutions, but finding them can only come with further experience.

I. OVERVIEW

Why am I here?

GOALS

There have been many computer systems developed which purport to let the user sketch using a computer. The user is placed before a console display of some sort, handed something which looks like a pen, perhaps is given some instruction in how to use the system, and is told to draw. It is reasonable to wonder in abstract, if one had such a system, what would he want it to do. There seem to be two answers: first, the system should help in the construction and storage of graphical images. Second, the system should act as an aide in the development of the information the sketch is meant to convey.

Under the first goal, when pictures can be constructed out of elements, saved, modified, and recalled at a later time, the designer has a useful time-saving tool for handling pictorial data. Repetitive elements need only be described once to the system. Representations of the complete structure can then be evoked with only a single stroke of the pen. Thus, instead of laboring hours over a drawing, the designer can describe the whole drawing to the computer using many previously defined elements, and the computer can construct the complete, finished work. Similarly, if two drawings are the same, with only minor

variations, the designer can construct one of them and store it away. He can then modify a copy of the saved image to match it to the second intended drawing, saving himself the trouble of constructing the drawing essentially twice.

More complicated than the first goal of a sketching system, one might ask a system to perform some more abstract operations on the sketch. A person uses sketches for two purposes: to convey information to other people which is difficult to transmit verbally, and to act as a sort of physical memory, in a sense, conveying information to himself. Once the sketch has been commited to paper, the user can modify it to change the information it contains. This act can be prompted either by the ebb and flow of the dialogue with the observer, or by a change in the sketcher's own idea brought about by the feed-back loop running between brain, hand, paper, and eye. In either case, the sketch is important because of the intended meanings it contains. In a similar way, it is useful for a computer system being used as a sketching tool to be able to attach some meaning to the objects being sketched.

The result of such a dialogue is that the information contained in the interaction is greater than the amount of information which could be contained in the sketch alone, or which the user could carry around in his head. Thus, one would like a computer system for sketching to be alert enough to be able to affect a

dialogue with the user. It would need to be knowledgeable enough about the subject matter being sketched to be able to ask reasonable (intelligent?) questions, and perhaps offer some information of its own. In short, the computer should be able to enter into a dialogue with the user, in much the same way as a person observing the sketch being created might interact. Such a provocative system would tend to maximize the amount of information generated in a sketching session.

OTHER SYSTEMS

Computer systems which have been developed to date tend to be divided into two classes, reflecting to a certain extent the two goals for a computer sketching system. The first class, historically, is that which uses some specialized set of functins, keys, or symbols in the process of sketching. Input was accomplished by invoking a function (key, e.g.), which told the computer what the user was intending to do, with the ultimate goal of permitting the computer to store, retrieve, and assist in modifying a drawing. In response to the user's request, the system performed some output which accomplished the action specified. The second sort of computer system seen uses a limited set of known symbols, and attempts to map the user's sketched ikons, usually drawn on a data tablet, into these symbols. In this case, the computer does not know in advance exactly what the user is going to do. What the user intended

must be inferred from the match of the sketched item to the known symbols, and the computer is usually expected to take some action as a result of the recognition of the symbol. Because of this level of guessing, such systems are not infallible, but this objection is matched by a comparable improvement in the ease of input (In the first class of sketch handling programs, it should be noted, the computer is incapable of making a mistake; only the user).

The most notable example of the first sort of program is Ivan Sutherland's SKETCHPAD (Sutherland, 1963), particularly since it was the first attempt at communicating a visual image between user and computer in an interactive manner. In its stated goals, however, SKETCHPAD was to be a system unlike drawing with pencil and paper, because interacting with a computer was seen to be a totally different kind of experience. Using primitives common to all line drawings (line segments, points, and arcs of circles), the user creates symbols, structures, and composites of these images. To increase the power of the interaction, certain functions could be applied to previously defined images. Thus, when the user laid down two lines, he could indicate to the system that he wanted them to be parallel or perpendicular, and the system performed the requisite steps to make them exactly that way. Thus, the user could be inaccurate in his original layout and yet get a highly specific output of his final image. Furthermore, since the user was not drawing symbols for the

system to recognize, the kinds of graphic images the system could accept was unrestricted.

For such freedom, the user pays a penalty, however. The system of light pen on display and function keys utilized by SKETCHPAD bears no relation to the normal means of communicating an idea graphically. The fairly demanding system of input required by such a system would tend to interfere with the creative thinking process. The user is concentrating so hard on getting the drawing into the machine that is difficult to think about what he is drawing. IBM is marketing a new system similar to SKETCHPAD which uses a tablet instead of a light pen (Saderholm, 1973). While this hardware is an improvement over the old setpoint-rubber-band-line, it still relys on a set of function buttons on the tablet to relay commands to the system. The degree of explicitness required in such systems quickly generates tedium sufficient to offset any prefererce over the less complicated job of digitizing the data. Any sense of natural graphical communication is lost. Furthermore, since the computer is operating continuously in "slave" mode, it can add no information to the dialogue. Thus, an important potential is lost.

In the second class of computer systems, the computer does add information of its own to the dialoge in its interpretation of the sketched symbols of the user. Although this approach is

primarily found in character recognition programs , perhaps the most notable example is the GRAIL system developed by the Rand Corporation (Ellis, et. al., 1969). Besides recognizing the alphabet and decimal digits, it could also handle a set of flow charting symbols (rectangles, triangles, and so forth), and lines connecting these symbols. Using the Rand data tablet, the user drew his flow chart and labeled it. As each symbol was drawn, the system identified it, and the rough display of the user's line was replaced by the machine's representation of the symbol, appropriately scaled and positioned. Because of the level of inference making, the program was capable of making mistakes. In order to allow for errors and to permit the user to change his mind, one of the symbols recognized by the system was the scribbling out motion normally used by people to cross out an error or a misplaced line. The symbol was called a "squiggle," and caused any line or symbol which appeared beneath it to disappear. Once the flow chart was completed, the user could ascribe specific functions to the symbols of the flow chart and see what happened when the flow chart was "run." It provided a neat way of seeing information which might otherwise have been too difficult to visualize.

Systems in the GRAIL class are quite attractive, since they provide a sort of interaction which is very natural and familiar to the experience of the probable user. Drawing with a pen on paper is an experience common to most people, and GRAIL's

replication of this experience is not bad. On the other hand, these pattern recognition systems can only handle a limited class of inputs. Given an unrecognizable symbol, the system is lost. This problem is partially overcome in many character recognition systems by having a "learning" mode, where the system samples the individual user's representation of the symbols it knows, thereby adapting its models for the symbols to the habits of the individual user. There are two limitations usually imposed, however. First, the user's representation usually can not deviate beyond some accepted boundary conditions. For example, a character recognition program normally accepts either script or printed characters, but not both. Thus, a user who mixes his characters would inevitbly be mis-understood. Second, it is usually impossible for the user to define symbols of his own. Thus, if a mathematician wished to user a character recognition system for the alphabet, he might be hampered by the inability of the program to accept Greek symbols; similarly, a Russian translator would have to start all over. Furthermore, as the number of symbols recognized by the system is increased, typically, the frequency of error increases at a much faster rate. This phenomenon occurs because the system can not use clues about the interaction between elements in a sketch. If a character recognition system had difficulty distinguishing between U's and O's, for example, it would be useful to look to see if the preceeding character was a Q (in English, anyway).

LETDOWN

It would be nice to be able to claim to have developed the alert, provocative, interactive system mentioned in the earlier section. The system which has been developed, HUNCH, falls short of this goal, however. Provocative it is, although not in the manner described above. It is also moderately interactive. It does not, however, carry on anything which can be called a dialogue. . .yet. Dialogue implies purpose and a developing context, and although HUNCH does know a few tricks, once it has performed, all it can do is walk off stage.

The name HUNCH is derived from the methods it uses to achieve its ultimate goal. It uses guesses about implied intensions to determine what the sketcher PROBABLY meant. In that sense, it is similar to the character recognition systems discussed. It does not have a set of patterns it is trying to match, however. Rather, it attempts to extract from the stream of input data the primitives which make it up: line segments, arcs of curves, end points of lines. Once the data has been so compressed and structured, these components can be combined to form objects of a higher order. This second step is not as well understood, since it requires extensive knowledge about the subject matter being sketched to accomplish this goal.

Because its knowledge is somewhat more limited than a human's, it would appear that HUNCH is at a disadvantage when it comes to reading a sketch. If it was limited to those cues available to human, that claim would probably be true. However, because of the way the data is collected, HUNCH can use some information unavailable to the human onlooker. Inherent in the way the data is sampled is the sequence in which the sketch was drawn, the pressure on the pen at a particular time, and the rate at which the user was drawing.

These cues provide additional information which the program can use to make decisions. In general, for example, the faster the user draws, the less accurate he is. Furthermore, if he is drawing rapidly, it can usually be inferred that he is not interested in the fine detail of his line, but rather in the grosser features of what he is drawing. When it encounters a rapidly drawn line, then, HUNCH is prepared to make bigger assumptions and to permit greater inaccuracies before declaring one line segment ended and a second one begun. Similarly, if the user is drawing slowly with great deliberation, then nearly every bend or tweak in the line is preserved.

Pressure can also be sensed to provide cues to the intentions of the user. Here, the role variations of pressure in a sketch is not so clear. It appears, however that pressure variations occur in quanta; a user typically draws in no more than three or four

pressure ranges. An initial inference is that pressure behaves something like inverse rate--that is, the harder a person pushes, the greater the detail implied. The cue to look for, however, is the quantum pressure change, not the small variations across a line.

WHAT HUNCH DOES AND DOES NOT

Sketching can be considered to be a kind of graphical language. A person can read a sketch if he knows the rules for making a sketch, and if he knows the symbols used in the sketch--syntax and semantics. In order to carry on a useful dialogue, you have to have both. The HUNCH system does a reasonable job at providing a large portion of the syntax. It is one of the goals of this paper to outline a means of supplying some of the semantics.

The sketch, as received by HUNCH, is one long serial stream of data. The system tries to apply some structure to this data, to make the search for meaning more manageable. In a sense, the solution developed so far still leaves the computer doing what it does well--number crunching. In the process of discovering the structure of the sketch, massive amounts of data are reduced to a collection of points and relations between points. It performs these operations with uncanny accuracy, using only local information about the dynamics of the line.

The relations formed are only those based on information explicit in the data, such as the aforementioned rate and pressure, continuity of line, and sequence. Attempts to apply further relations to the data failed for various reasons described later, and in fact, appear inevitably doomed without the application of some semantic guides. Some of those relations attempted include latching of two known points, and horizontalizing and verticalizing lines in a sketch which appear nearly so. These functions failed largely because HUNCH was unable to judge those situations in which those relations might or might not apply. Thus, it applied them indiscriminately to any set of lines which fell within its guide-lines. The result inevitably was a severe distortion of the original sketch. Parenthetically, it should be noted that if input was limited to those sketches where the rule was always appropriate, HUNCH solved the problems with distinction. Thus, the problem was not in the rule, but in when to apply the rule. Given any rule, there is always a condition where, applied indiscriminately, the rule will fail (including this one). Thus, some means is needed to guide the system about when a particular relation might be appropriate.

The final output of the system is not intended to be a "working drawing" with all extraneous lines eliminated, all corners squared, and all lines straight and parallel. Rather it is intended that the output be the description of the sketch which

might correspond in some way to the verbal description a human might make of the sketch having observed it. The structure of this description would be hierarchical, having at its top the major features of the sketch, at its interim levels the elements which combine to make up these features, and at the bottom the individual line segments of which the sketch is made. The interaction of the various elements in the description provides contextural information. This information can be used to augment the rules about relations between lines which got us into trouble before to provide the guide-lines about when a particular rule might be applied. Furthermore, it helps to avoid the difficulties systems of the GRAIL class get into when called upon to recognize a large number of different elements. The context limits the number of plausible elements which may be used, preventing the system from drifting too far afield.

Unfortunatiely, this desirable description has not been implemented in any form. In order to derive such a description, the system needs to know what the elements are for which it should be searching (wired in to most systems). While in most types of sketches the number of these elemetns is not large, it has never been clear how one would specify these elements for the system. The description offered in the last section of this paper is a first attempt at making such a specification possible.

HARDWARE USED BY HUNCH

HUNCH runs on the Architecture Machine, a family of Interdata mini-computers, running under a disk resident operating system. The original sketch is read from a Sylvania data tablet, and can be stored on a variety of mass storage devices. The Sylvania tablet is (was) the Cadillac of data tablets, offering resolution to three thousandths of an inch, constant rate data sampling, and a clear tablet. This clear tablet means that it can either be drawn on as with other tablets, or it can be placed in front of the display and used in a manner similar to a light pen. Both of these modes are used by various parts of HUNCH. The tablet samples data at a constant rate (two hundred times per second), sending off to the computer twelve bits of x- and twelve of y-coordinate data at each sample. The tablet can also sense a limited capability for a z-dimension (three bits), such that it can tell if the pen is touching, is in the near field (about one half inch), is in the far field (up to four inches), or is away from the tablet. This feature suggested a logical extension, and the pen was modified to be able to sense pressure--how hard the penman is pressing on the paper. A load cell (a sort of transverse strain gauge) has been built into the shaft of the pen, taking the thrust from the top of the ball point pen cartridge. It can measure pressure from a fraction of an ounce up to a pound. This load is converted into a digital signal which is sent as a six-bit number to the computer. Each pressure

sample is associated with the point read when the sample was taken.

The display is not crucial to HUNCH, although it is useful for demonstration and debugging purposes. Because of the amount of data developed by the data tablet and the complicated pictures possible, it would be impossible to maintain a flicker free image on a refreshing display. After ten seconds of drawing, the screen would have two thousand vectors on it. HUNCH uses an ARDS storage tube, which effectively avoids this difficulty. Although it is difficult to dynamically modify the image on a storage tube, there is very little need to do so in a sketching environment. The difficulty of erasing is not unlike that the user experiences when drawing with pen on paper, anyway. Rather than erasing, the user just gets a clean sheet of paper. The ARDS has a limited dynamic mode, called write-through, which permits the dynamic alteration of a limited number of lines. This feature is adequate for those rare occasions when a picture must be modified.

While the sketch is being initially stored, it can be displayed in an exact mimic of the original. The ARDS is a relatively slow display, however, and the time taken to display the image reduces the sample rate which can be obtained from the tablet. Thus, the resulting stored sketch is less detailed. To overcome this difficulty, display while drawing can be suppressed. The stored

sketch can, of course, be replayed to the display. During times when the pen is not touching the tablet, a real time clock is sampled, so that the length of pauses in drawing can also be stored. The replayed sketch, then, can be an exact replica of the dynamic development of the original.

The addition of pressure sensitivity demanded an additional feature for the data display--some method for showing variations in pressure. The ARDS was altered such that its focus could be modified under computer control. Thus, while the tube normally displayed a thin, sharp line, by defocusing the beam slightly, the width of that line could be increased up to an eighth of an inch. This feature is integrated with the load cell in the pressure pen such that the width of the line varies as a function of the (original or redisplayed) pressure (Figure 1). This line variation greatly enhances the visual effect of the display, since it provides a better feel for pressure than the line output of a ball point pen can provide.

Figure 1.



II. PAST

How Did I Get Here?

READING AND REDISPLAYING--DRAW/SHOW

In the spring of 1970, the Architecture Machine Group obtained its Sylvania tablet, and embarked on an experiment to discover about reading a sketch by computer. The tablet was an ideal device for this experiment, having the natural feel of pen on paper, while at the same time providing a fast, accurate, time-dependent sampling of the sketch as it was created. The first programs written, naturally enough, were programs to read and save the data from a sketch, DRAW, and to redisplay the stored data, SHOW. DRAW senses the z-position of the pen, only recording data when the pen touches the tablet. The maximum distance the pen is away from the tablet (near or far field) is recorded as a flag in the stream of data whenever the pen leaves the tablet. The distinction of the z-fields is not used by any part of the program to date. It is thought, however, that the degree of pen lift may be useful for providing some clues into logical separation of the sketch into sub-sections, divided by higher lifts of the pen.

Where the pen went while it was not in contact with the tablet could be read from the data, and there was some discussion at the

time about whether or not this information should be saved. Since at the time, we did not know what information was going to become important, we were leery of discarding any obtainable information. The use to which pen-up information could have been put was unclear at the time (it is still so), however, and space limitations for storage of data were relatively severe at the time. It was decided, therefore, to discard this data.

DRAW begins by sensing the position of the pen in the z-field. When the pen touches down, DRAW records a far-field pen-lift flag and the x- and y-coordinates of the first point. With the recent addition of pressure sensitivity, the value of pressure is also saved. It then continues to read successive points and pressures, storing them away and (optionally) displaying them on the storage tube. When the pen is lifted from the tablet, DRAW waits for the pen to be replaced and saves the pen-up flag recording the farthest field reached by the pen and the time the pen was lifted. DRAW continues to read and save data in this manner until the pen is lifted away from the tablet field and then signals that the drawing is complete.

Once the data has been saved, it can be redisplayed by a call to the program SHOW. When this program was run for the first time, it caused the sort of serendipidous discovery which occasionally provides direction for research. Although it seems obvious in hind-sight, the effect the time based sampling of data would have

on the data itself had not occurred to anyone. Since the tablet samples data at a constant frequency (200 times per second), the distance the pen covers between samples is a direct function of how fast the pen is moving. Obviously--now--the faster the pen is going, the greater the distance it will cover in a two hundredth of a second--the farther apart the recorded points will be. The effect of this fact, of course, is that SHOW not only redisplays the original sketch, but also it replays the sketch at exactly the same rate it was originally drawn. Inherent in the way the data is stored is the data is stored is the RATE at which the line was drawn.

This fact provided the ground on which HUNCH is built. It may be assumed that the speed at which a person draws reflects in some way his degree of purposefulness, his detailed interest in exactly what he is sketching. More specifically, it is usually true that if a person is drawing quickly, he is not as interested in detail as he is when drawing slowly. In a quick sketch, the person is usually interested in the general impression his lines make, rather than in the exact reproduction of those lines. Conversely, a slowly drawn sketch may often be painstakingly detailed. In this case, the position of each line becomes important, and the sketcher wants his drawing to be seen exactly as drawn.

SQUIGGLES

One special purpose kind of line is detected "on the fly." As mentioned in the description of the GRAIL system, the scribbling out motion has a special meaning. If drawn over previously drawn lines, it means that the earlier lines are to be crossed out. If filling an open area, the scribble implies that the area is to be shaded. In either case, the exact configuration of the line is not as important as the area it covers. Thus, it is not critical to submit the line to exact analysis. In order to extract these scribbles from the raw data, a "squiggle" recognizer was devised as a part of IRAW. Coincidentally, Rand's use of a squiggle, even the to the name itself, was not discovered until after the one in HUNCH hac been developed.

A squiggle is characterized by several things. First of all, it has many changes of direction. It is usually drawn at a fairly high rate of speed, however, so it is not confused with the curving line of a driveway, for example. Finally these changes of direction form a sawtooth pattern (they are neither too spread out nor too sharp), so that a squiggle is not confused with a wobbly fast straight line nor with a line which has been heavily overtraced (Figure 2).

When the pen is placed on the paper, the squiggle recognizer begins searching the data as it is read for sharp changes of



Figure 2.



Figure 3.

direction, called extremes. Since a squiggle must be drawn quickly, the program expects to find many of these extremes before many points have been read. In fact, if the required number of extremes have not been found before a maximum number of points have been read, the program decides that the line is not a squiggle, and it quits looking. If the requisite minimum extremes do fall within the limit, then the position of these extremes is examined for the sawtooth pattern. If the extremes are too spread out or too close together (separated by angles greater than 9 degrees or less than 10 degrees), then the squiggle is rejected. Finally, the total rotation of lines connecting the extremes is compared to some maximum allowable value. If it falls above this maximum, the squiggle is rejected (this check is added because the person who implemented the algorithm objected to the fact that flowers were recognized as squiggles (Figure 3)). Having passed all these tests, the line is recognized as a squiggle. The beginning point of the line is tagged, so that subsequent programs can recognize the line as a squiggle to be treated as a special case.

EXTRACTING LINE SEGMENTS--STRAIT/STRAIN

After the discovery of the rate dependence of the data, it was decided that the next step PUNCH should undertake would be to try to extract from the original data the straight line segments of which it consists. It would make its decisions by searching the sequential, raw data for "significant" changes of direction, tempering these decisions by taking into account the rate (and later the pressure) at which the line was produced. A more detailed account of how this program works follows in Section III. This section covers how the program arrived at the state it is in now.

The original attempt at a solution was a set of programs which eventually became known as STRAIT. This original version calculated the tangents of segments defined by connecting pairs of points in the raw data. It then looked for differences in these tangents, comparing the change in tangent to some value. If the change was greater than this threshold value, it was determined that one segment ended and another began. This solution quickly turned out to be a mistake. Because the tangent is so non-linear (going to infinity for a vertical line), the threshold level had to vary as a function of the direction of the segment. Furthermore, when dealing with infinity on a finite state machine, one quickly becomes embroiled in roundoff and overflow difficulties. As a result, this original approach was

abandoned, and a calculation of the arctangent of the segment was substituted. Except for a discontinuity in the arctangent function around zero radians, it has the attractive feature of being linear everywhere else. Thus, the threshold problem became direction independent. Furthermore, since the arctangent is limited to values between zero and two pi, the difficulties with infinity were eliminated.



Figure 4.

It is the nature of a sketch that although a sharp corner is intended, it is rarely achieved. Instead, the two segments meeting at the corner are connected by some circular arc. Furthermore, since the drawer has to slow down in order to negotiate the corner and still be drawing where he intends afterwards, points tend to collect at corners. As a result of these facts, the first point fallin above the threshold for a corner could not be assumed to be the actual intended position of the corner. In fact, because the (sharp) corner might actually be represented by an arc, there is no guarantee that the intended corner exists in the data at all (Figure 4). The only reliable way of determining the intended position of a corner is to determine the two segments lying on either side of the corner, and then to calculate algebraically the intersection of these two

lines. This was the approach taken in STRAIT. Once a segment has been discovered by an instance of a change of arctangent greater than the threshold, its endpoints are saved. When a second segment is found, then, the intersection of the two segments is calculated and used as the common endpoint of the two segments.

The result of such calculations is the creation of points and links between points which represent lines. When a pen-lift flag is found, the points on either side of it are saved as the end and the beginning of a segment. When the position of a corner is calculated, that point too is saved. To represent a line between two points, a link is created which contains information about which two points are connected, the rate at which the particular line was drawn, and the greatest pressure reached across the line. This structure is the output of the program STRAIT.

In order to cut down even further on the amount of data to be saved, and to maximize the inferred information in the final structure, STRAIT had a program which looked for implied "latches." When two points fall near each other, people will often mentally connect them as if they were a single point. STRAIT tried to do the same thing. In Figure 5, the first and last point of the line fall near each other. STRAIT decided that they were intended to be the same point, and latched them (The raw sketch appears at the beginning of Section IV).



Figure 5.

The method for performing this operation is similar to that for finding corners. Each time a new point is determined, the list of existing points is searched for points nearby. In order to be considered near, the distance between the new point and each point on the list is compared to some threshold limit. If the distance is less than that threshold, the point is considered near. If no point falls below the threshold, then the new point is added to the structure with the appropriate link to any points which may be related by lines. If at least one point is found below the threshold distance away, the nearest point to the new point is considered to be the intended match. Links are created between this point and any related points, and the new point is not saved. Initially it was thought that the tendency would be for people to draw lines to known points, so the initial position of a known point was unmodified, and the direction of the new line was modified to take it to the known point. Subsequent experience seems to indicate that people tend to correct earlier errors in positioning points by drawing subsequent lines to where

the point should preferably have been. A somewhat better treatment, therefore, would have been to move the old point to the position of the new point, or at least to average the two points somehow. Difficulties with the whole latching scheme later tended to render the whole approach suspect, however, so this minor modification was never implemented.

The output structure of STRAIT, then, represented the minimum number of line segments and points which could describe the sketch, subject to some threshold values. For certain classes of sketches, this assumption proves to be entirely adequate; using these simple principles, STRAIT's handling of such a sketch is remarkable (Figure 6). STRAIT had several severe short-comings, however, which tended to point away from its existing mode of operation to some more complex handling of the data.

One difficulty came in the problem of handling overtracing. The tendency to retrace a line already drawn is a normal behavior on the part of a human user of the system. The method for finding corners was inadequate for handling the small angles commonly resulting from retracing a line. The precision of the computer was inadequate for sharp angles, due to roundoff errors and a tendency to wind up dividing by zero. Calculating the algebraic position of a corner between two lines which are nearly colinear resulted in frequent, severe misplacing of the common point. To combat this difficulty when calculating a corner, an additional



Figure 6.

routine was added to check specifically if the angle between the two lines was very small. For a small angle, using the calculated intersection is dangerous. Instead, an effort is made to find the point at which the line changed direction--the locally extreme point on the line. In such an instance, this extreme is used as the common point between the two segments. In the case of a sharp angle, the corner can not be very rounded, so the error induced by using a real data point on a corner is small. Unlike the case of a wider angle, furthermore, such an error causes little change in the direction of the line (this fact, after all, is what makes calculating the intersection so difficult).

The introduction of overtracing causes a vast proliferation of segment endpoints in a sketch. One of the restrictions on the class of sketches STRAIT could handle well is that the sketch must have a fairly diffuse distribution of corners and endpoints. When the density of points increases locally, then segments begin to become wrongly latched (see Figure 7, the proverbial sketch of Aunt Fifi's house). The addition of overtracing only



Figure 7

aggravates the problem. The decision to latch or not to latch is not a purely local decision. Who should have authority to make such a decision is a point which is still under debate. The last part of this paper is one proposal at a solution. At any rate, it seemed futile to try to continue with the solution used by STRAIT, so a variation was developed which eliminated the latching step (STRAIN, STRAIghten with No latching). This seemingly backward step is justified as a basis for the groundwork for future development. We already know one method which will not work.

RATE/PRESSURE

Mildly glossed over in the above discussion of finding straight line data was the role that rate and pressure played. The original version of STRAIT had no measurement of rate or pressure; the various threshold values applied were constant throughout the program. After the basic routines were functioning more or less correctly, a method for figuring rate was determined (see description in Section III). Once the rate that a line had been drawn was calculated, that value could be applied to a function for figuring the various thresholds. Nominally, for a faster line, the thresholds were higher. The effect of this additional function on STRAIT was striking. There was an immediate, marked improvement in the decisions STRAIT was making about the data. In order for earlier versions of STRAIT

to work, the thresholds had to be set quite low to allow for the comparatively small changes of direction which occur when a line is being drawn slowly. Similar difficulties arose for latching. The effect of this limitation was to cause STRAIT to permit many more corners than were actually intended. If the thresholds were increased, STRAIT began to miss intended corners on slow lines. The addition of a rate measurement permitted application of a more liberal threshold for fast lines, a more conservative one for slowly drawn ones.

One side effect of this treatment was that STRAIT (and also STRAIN) became fairly sensitive to the "hand" of the user. Different individuals have different styles of sketching. Some people can sketch quite accurately at a very high rate of speed; others are not so accurate. Thus, the value of the thresholds for one person at a particular rate might not be appropriate for another person at that rate. In a pathalogical case, one can imagine a person who drew quite smoothly when moving his hand rapidly, but who suffered from palsey when moving his hand slowly. In order to work properly for an individual, then, STRAIT has to be tuned to each user's hand. Several methods for discovering the proper tuning for a particular person have been tried. The only one which works at all successfully is intuitive manual adjustment of parameters.

One program was written which tried to to the tuning job implicitly. The way the value of a threshold is determined is by applying the rate to a polynomial function:

```
TH=A*(Rate)**3+B*(Rate)**2+C*(Rate)+D
```

Rate varies between a value of zero and a value of fifteen. The various parameters (A,B,C,D) are a function of the hand of the indivual user. Because of the complexity of tuning the parameters manually, the value of A was normally set to zero, reducing the polynomial to a quadratic. In such a case, the effect of the various parameters can be seen to be as follows:

At low rates, D predominates.

At high rates (assuming the value of B is a small fraction), the C term is dominant.

For the middle ranges, the value of the fraction B determines which way the function curves and the degree of curvature.

It was thought, then, that the various parts these parameters played at various rates could be separated and treated individually. Thus, the tuning program asked for a set figure (a square) drawn at a slow rate. It then juggled its D parameters until it got a four-lined, four-cornered figure. The program then asked for a quickly drawn square, and modified its C

parameter until it got a value that made the figure fit. Finally, it took a square drawn at a moderate speed and set the B parameters. While the program frequently could come up with a solution, almost equally often it could not find a value for one or more of its parameters which was satisfactory. Part of the problem derived from the limits which had to be placed on the values the parameters could take. In order to provide some starting point for the program and to prevent the arrival at some totally unreasonable parameter values, each of the parameters had an upper and a lower bound for the values it could take. In many cases, however, rather than settling on an intermediate value for a parameter, the program had a tendency to slide to one limit or the other. To compensate, the other parameters would become equally skewed. It is difficult to speculate on why this error tended to occur, but it appears likely that it was caused in part by the inter-relation of the parameters. Experience in manual tuning of the parameters seems to indicate that it may not always be true that the parameters can be separately tuned. Occasionally a better set of parameters was arrived at if, while increasing the value of one parameter, another parameter was comparably reduced. Since the implicit tuning program knew nothing about this technique (which appears to be largely intuitive, anyway), its results were often inadequate. At any rate, that particular experiment has been abandoned.

With the ability to sense pressure, a new variable has been introduced into the system. How this parameter should affect the behavior of HUNCH is not certain yet, as we have not lived with it for very long. It seems reasonable to assume that a heavily drawn line requires more detailed analysis than a light line. This effect can be accomplished by using pressure to offset rate. As the pressure increases, it applies more drag to the line, slowing down the calculated rate. Thus, a quickly drawn line, drawn at great pressure, receives as detailed an examination as a slow and deliberately drawn line at any pressure. The rate is made to vary as a function of pressure according to the equasion:

$$\text{Rate} = \text{Rate}^{*} \frac{16 - \text{Pressure}}{16} \qquad (0 < \text{Pressure} < 15)$$

This function has the interesting side effect that its impact varies as the rate it is operating on changes. At high rate, a moderate change in pressure (say from zero to four) cause a comparative change in rate (from fifteen to eleven). At a slow rate, the effect is less (three to two, e.g.). This fact is rather attractive, intuitively, but the overall effect has never been evaluated.

INTERSECTIONS--INSECT

Because of the way the data is generated and stored, there is no reason to believe that if two lines cross each other, their intersection actually exists in the raw data. This problem aside, in the process of searching for straight line segments described above, it is impossible to find intersections at the same time. Nonetheless, it is not unreasonable to want to know about the existence of intersections. In fact, for some applications, the finding of crossings and related T-intersections, is a great aid toward solution of the particular problem (Negroponte 1972). In order to locate these points, then, a program to find them was developed, INSECT (from INterSECTion).

INSECT uses a brute force method for locating intersections of lines in a sketch. The first line discovered is compared to all the other lines found, and the algebraic intersection of the line and each subsequent line is calculated. As these points of intersection are found, they are compared to the endpoints of the two lines being worked on to see if the intersection falls between, or within some delta (varying according to rate, as usual) of the endpoints. Intersections falling outside these limits are discarded. Those falling within the limits are considered to be discovered intersections (Figure 8). If the intersection falls within the threshold of one of the endpoints



Figure 8.

of the two lines, that point is moved to the coordinates of the intersection, the other line of the pair is broken, and the endpoint is made the common end of the two new segments. If the intersection falls well within the ends of the two segments, a new point is added to the structure, and both lines are broken and attached to it. The second line in the structure is then compared to all subsequent lines; the third; and so on. The resulting structure has all intersections and T-joints inserted in appropriate places in the straightened version of the sketch.

It can be seen that the amount of calculation which must be done by this method goes up as the factorial of the number of lines in the sketch. This load is clearly unacceptable. As a sketch becomes more complicated, with overtracing for example, the amount of calculation goes up astronomically while the number of useful results does not. It seems reasonable to say that we are

willing to make N linear passes through the data (where N is a small integer--we are willing to look at each line N times), but we do not wish to pay the cost of even one pass through the data which is worse than linear. It took a long time to come up with a solution better than INSECT for finding intersections, and the better method has not been implemented yet.

We have a method for mapping a sketch, raw or straightened, on to a large array (existing on a fast-access fixed-head disk). For a complete description, see Appendix II. With a bit of cleverness, the straightened data can be mapped into two grids (or one two-bit grid), such that if the mapping program discovers that the bit in the first grid is already on (a bit being a point on a line in the straightened data), it turns on the equivalent bit in the second grid. It can be seen that, if every line in the straightened data is mapped on to the grid once, the only points which could appear on the second grid would be those points where two lines intersected. Thus, in order to include the intersections in the data structure, it would be simply a matter of reading points from the second grid which relate to lines in the straightened data. If a bit is found to be on, then, it is an intersection, and the coordinates of that point could be inserted into the line currently being tested. The extration of all intersections would require only two linear passes through the data for a complete solution: one to map on to the grid, one to read for intersections.

It should be obvious that this solution does not find T-joints which were near misses (Figure 8A). This objection is not entirely bad, however. Since the method for finding T-joints in INSECT used the same kind of "latching" described for STRAIT, it was prone to the same kinds of difficulties. Essentially, this problem comes up whenever there is an attempt to apply a local decision to a situation which requires more global information. This error occurs where there is an attempt either to remove or to add information which can not be directly derived from the available raw data, where the data is extrapolated across empty space. Thus, the loss of this "missed T-joint" capability only parallels the removal of latching which turned STRAIT into STRAIN. If one wished to recover this ability for some particular application, one could take windows off the grid around the points in a sketch and look for lines which cross these windows.

HORIZONTALIZING AND VERTICALIZING--LEVEL

In an architectural context, lines which are horizontal or vertical have special meaning. This effect occurs because we live in a gravitational system which makes building horizontally or vertically a more reasonable way to construct buildings than any other way. Since the applications for HUNCH were considered to be primarily architectural, it was decided that it should be able to place a special meaning to lines which were horizontal or

vertical. The program LEVEL was written to search the straightened data for lines which could be implied to be horizontal or vertical. It calculated the restricted arctangent (between zero and pi/2) of each straightened line segment, and compared it to a pair of rate-dependent threshold values. If the line fell above the upper threshold, it was considered to be a vertical line, and the coordinates of its endpoints were adjusted so that the line was forced exactly vertical. Similarly, if it fell below the lower threshold, it was eventually forced exactly horizontal. This program attempted to take into account the implied continuity of lines. If one line was found to fit one of the thresholds, the lines connecting to the points on either end of the segment were examined to see if any of them fit the threshold the same way. If a line was found continuing in the same direction, its second endpoint was also searched for a continuing line. This process was repeated until no further continuing lines were found. Then the positions of all of the points found to be part of the continuous horizontal or vertical were adjusted at once, so that the



Figure 9

continuity was preserved (Figure 9). This need arises from the desirability of preserving continuity, and from the danger of moving one point without examining the points around it. There could exist a condition where a line which falls outside of the thresholds is moved within them by the leveling of one of its endpoints being acted on at another segment. Thus, if the points were adjusted independently, information from the original data might be lost by the partial treatment of a line segment. This approach made LEVEL perform as well as it could be expected to, but since it used the same extremely local information about line segments that latching and intersection finding do, it suffered from the same kind of indiscriminating errors that those two functions make. Thus, while serving as an educational and jazzy exercise, its usefulness is questionable.

CURVES

One of the first decisions made in the development of HUNCH was on the subject of cureves. Curves are somewhat more difficult to handle than straight lines, since they are more difficult to define. A straight line, after all, can be represented by two points. A curve requires at least three, and it is not at all clear which three are appropriate. Furthermore, in a sketch, it was difficult to come to grips with the problem of differentiating a curve from a wobbly straight line or from a very sloppily drawn corner. In Figure 10, for example, it is

not even clear to a human whether that is a sketch of badly drawn rectangle or of a a super-ellipse.



Figure 10.

As a result of these difficulties, it was initially decided to side-step the issue by refusing curves as valid input. This decision can be partially justified on the grounds that, in the assumed architectural context, curves just do not occur that frequently. Avant guarde architects aside, the vast majority of buildings have straight walls and flat ceilings (Negroponte, 1973). Thus, while ignoring the problem of curves imposed a limitation on HUNCH, the resulting simplification of the goals seemed to get us a long way before it became a problem.

The immediate goal of HUNCH, then, was to look for straight lines. The approach used has a rather interesting side effect if the program is presented a curve. Since corners are defined by finding two line segments and calculating their intersection, a curve becomes simply a very long corner. Once a curve starts, no further action is taken by the straightening program until the curve ends. This fact makes the operation of HUNCH on curves rather unpredictable. In fact, it may be said that the way HUNCH operates is the worst possible way to handle curves there is: HUNCH will make worse decisions about curves than any other method of data reduction from sketches. The most extreme case of

failure is shown in Figure 11. In 11A, HUNCH found a straight line segment at the beginning at at the end of the stroke. They have been emphasized in 11B. It decided that everything in between the two segments was a corner, and calculated the intersection of the two segments, to define the position of the corner between the two segments. The results are shown is 11C.

While the initial assumption about the importance of curves still appears valid, over the years it has become a bit of a thorn in the side. The first thing anyone does in a demonstration of HUNCH is to throw a curve at it. As a result, it was decided to try to find a method for at least recognizing curves. If HUNCH knew a curve existed, that would be sufficient to keep it from being confused. Furthermore, in a sketch, the actual shpe of a curve is not as important as is the recognition of its existence. The user is not likely to care whether the curve is a parabola, circular arc, sine curve, or part of a complex polynomial. He will care if it gets straightened, however.



Figure 11.

The initial approach taken to try to recognize curves was to use the mathematics of the line to cause the curves to stand out. The slope of a sketched line (its first derivative) changes along its length. In the case of a straight line, the variations are small around some constant value. At a corner, the first derivative undergoes a discontinuity. For a curve, the first derivative is constantly changing, smoothly. If one looks at the second derivative of a line, then, that of a straight line will be zero, or nearly so. A corner would have a spike around the discontinuity, and a curve would be identified by some fairly uniform, non-zero value. Unfortunately, due to the method of sampling data, the theory does not work when put into practice. Local variations in the data tend to over-ride the actual data from the second derivative. Figure 12 shows some samples of sketches and the first and second derivatives associated. Any positive value in the second derivative is lost in noise from the data.

Another approach which shows more promise is to capitalize on the poor curve handling ability of the straightening pass of HUNCH. One way to make HUNCH handle a curve better has always been to draw it more slowly, since that would cause the curve to be segmented into smaller lines. In fact, small variations in the parameters used to determine the minimum bend which defines a corner result in radically different behavior of HUNCH on curves while having only minor effects on the analysis of straight



Figure 12



Figure 13

lines. Figure 13 shows a sketch consisting of both lines and curves, and three analyses by HUNCH of the sketch, using different rate parameters. It can be seen that while the variation of the analysis of the straight lines is slight, there are vast differences in the handling of the curves. Note that the handling of the rounded corner (at (a)) is done correctly in all cases. The implications of this discovery are not fully investigated yet. Although this approach was first proposed over a year ago, it was not tried until recently, after the first approach had been thoroughly discredited.

EDITING

Since HUNCH frequently makes mistakes (largely due to objections previously discussed), it seemed desirable to implement a means of editing the resulting structure. Since this editing was ultimately accomplished by explicit commands, their implementation has no direct bearing on the philosophy behind HUNCH. Their description is included for completeness, however.

To edit a sketch one needs the ability to perform four functions: the ability to add a point; the ability to remove a point; the ability to link a line to a point; and the ability to break such a link. The workhorse of the editing package is a program called MOVE. By pointing with the stylus of the tablet, the user can grab a point in the displayed structure and move it

to some other position in the display. If the new position falls close to another point, all the lines attached to that point are latched to the newly positioned point, and the other point is deleted. A point can be slid down a line that it is on until it becomes latched with the other end of the line and the extra point deleted. Points may also be deleted by a program called CLEAN, which eliminates slight bends in otherwise straight lines. Since this process over-rides a decision made in the straightening pass, however, this program is extremely timid

To add a point, there is a program called BEND. If the stylus is pointed at the line to which the point is to be added, the line is broken, and a new point is added to the line at the location indicated. This point may then be moved or latched, as in MOVE

Finally, there is a program called DETACH which breaks links between points. The user draws a line across those lines in the display which he wants detached from a given point. A new point is created, offset slightly from the point in question, and the crossed lines are detached from the old point and latched to the new one. The program decides which point is to be detached from by finding the common endpoint of the lines drawn across. If there is only one line crossed, it decides which end of the line segment the intersection is closer to, and detaches from there.

III. PRESENT

Where Am I Now

Let us step through HUNCH's resolution of a sketch. The user invokes the command DRAW, and draws Figure 14, a rectangle. The drawing was done in one stroke in a counter-clockwise direction from the upper right. He signifies that the drawing is complete, and the file containing the data is closed. The actual data points stored by the program are shown in Figure 15. The distance between the points gives some indication of the rate at which the line was drawn. It can be observed that the first half of the square was drawn at a fairly rapid rate, while the last half was drawn more slowly. Since the pressure sensitive pen was not available when this sample was taken, the pressures associated with the data in this sketch are all zero.



Figure 14.



Figure 15.

The sketch is now ready to be examined for straight line segments. This pass at the data is described as separate from the DRAW routine, but there is no inherent reason for the two operations to be separated. With minor modifications, the command STRAIN could be integrated with the draw phase. In that case, the search for line segments could be done "on the fly." Under the present scheme, the straight line finding pass at the data is invoked by the command STRAIN.

The body of the work in finding line segments is bound up in three routines: NOEND, TANGNT, and TRNTST. These routines provide the main interface between the program and the raw data, and they are usually called in sequence, in the order they were named above. NOEND performs lookahead, data management, and parameter setting. TANGNT, a slight misnomer from historical reasons, calculates the arctangent of a line over a segment. TRNTST determines the difference between two successive arctangents.

NOEND is perhaps the most subtly complicated program in the system, since it apparently does so little and is responsible for so much. The first thing NOEND does is to call the routines which calculate the current applicable rate and pressure. RATER does not calculate the rate at every point, since the rate does not fluctuate greatly over a very small area and since the method of calculating rate works over a range of points around the

current one. In order to minimize the effect one anomalous point could have on calculateion of rate, a method of calculation was chosen which examines points near the current point. Rate is considered to be an inverse function of the number of points sampled before the line has traveled some set distance, approximately three eighths of an inch. The current point pointer is temporarily backed up a few points, so that the sample will likely fall across the current point, rather than one side or the other of it. Then a points traversed counter is bumped, and the distance between the new current point and its following point is calculated. This length is compared to the fixed distance, and if greater, the calculation is complete. Otherwise, the current point counter is incremented, the counter bumped, and the next distance is calculated. The length of this segment is summed with the length from previous calculations, and the sum is compared to the fixed length. This process is repeated until either the fixed length is exceeded or until the points traversed counter exceeds sixteen. The difference between the points traversed couner and sixteen equals the rate (0-15, a reputable computer-based numbering system). The pressure at the original current point is then normalized to fall in the 0 to 15 range as well, and this value is applied inversely to the rate (see Section II, Rate/Pressure).

This calculated rate is then applied to the user's parameter polynomial,

```
TANDIF=A*Rate**3+B*Rate**2+C*Rate+D
```

where A, B, C, and D are parameters unique to the user for this application of the function. TANDIF is the maximum allowable change in arctangent before STRAIN decides that a corner was intended. Thus, the degree of turn which determines a corner is a function of the individual user and the local rate he is drawing at any given time.

The next task NOEND has is to check to see if it is going to run out of data. STRAIN is going to calculate the arctangent of a segment connecting the current point to a point some interval down the data (usually two points away). The reason for using this interval, rather than simply calculating for the segment between the current point and its successor is that such an approach would make the program to susceptible to local jigs in the line. By skipping a point or two in between, extremely local variations in the line tend to be smoothed out, while major changes in direction are unaffected. However, there are two events which must be watched for across this interval. First, since the data exists in a fixed buffer, NOEND must check to make sure that the end of the buffer has not been reached. If this is the case, the ramaining data in the buffer is flushed, and more data is fetched. Second, and more important, the data across the interval must be checked for "pen-up" flags. Such a flag indicates that the line being looked at has ended. If a pen-up

flag is encountered, a special exit is required to a subroutine called ENDSEG. At the end of a segment, no more calculation can be done on the current line, so loose ends must be tied up, and the program must be reinitialized to begin a new segment. ENDSEG will be discussed later.

NOEND has one more function to perform; it checks for extremes on a line. As it examines the points on the line, it sends each point to a subroutine called EXTRMR. This routine checks to find out if the line has changed direction more than ninety degrees over the last few points. Such an occurrence is called an extreme. If searching for extremes seems redundant to the main-line search for corners, it is. The information developed by EXTRMR is used later by subroutine CFSA (Check For Small Angles), however, and therefore must be found. Note, this EXTRMR is the same as the routine called in the search for extremes defining squiggles.

Finding no ends of lines across the next interval, NOEND loads the x- and y-coordinates of the current pointer value it was handed (or the first point in the new buffer, if the end of the buffer was reached), and returns. The next step is a call to subroutine TANGNT. This routine increments the current point counter by the interval (two points), and gets the x-length and the y-length for the segment between the previous and the new current points. Using these values, TANGNT calculates the

arctangent of that segment, resulting in a value between zero and two-pi. This number is added to the top of a circular list of arctangents for later access, and TANGNT returns.

The third member of the trilogy, TRNTST, obviously can not be called until TANGNT has been called at least twice. After the second call to TANGNT, the list of arctangents is handed to TRNTST, which calculates the difference between the top two arctangents on the list. Because of the discontinuity of the arctangent function around two-pi, TRNTST has to worry about lines in this vicinity (a pair of nearly colinear, horizontal lines could return an arctangent difference of nearly two-pi). The exact difference of the arctangents is not as important as the magnitude of the difference, so TRNTST gets around the discontinuity by returning the lesser value of the following functions:

```
Difference=|Arctangent(1)-Arctangent(2)|
      =2*Pi-|Arctangent(1)-Arctangent(2)|
```

It can be seen that in the horizontal line case, the routine would return the correct value.

The power of these three routines can be shown by seeing how STRAIN uses them in its search for line segments. The first buffer of data is fetched and the currnet point pointer is set to

the first point in the buffer (194,x;540,y in the sample sketch). STRAIN is going to try to deal with two line segments at a time.

1) Since the first point obviously begins a segment, its x- and y-coordinates are saved in an array called THOLD; a pointer to this location is stored as the first element in a second array called CORNER; and a pointer to the point's sequential position in the original data is stored as the first element in an array called DATP. Furthermore, a flag is set in RATE to signal that a new TANDIF parameter should be calculated, and a call is made to NOEND. Since the interval is currently set to two points, no endpoints or end of buffer is encountered. The rate is found to be 14, the x-coordinate 194, and the y-coordinate 540. When stored, the maximum rate reached while drawing the line segment is associated with the line for furture reference. Since this is the first data examined, the associated rate must be the greatest found, so it is set aside for later comparison. A call is made to TANGNT, and the arctangent of the first segment, between the first and third points is calculated (6.27) and stored on the circular list TAN. This arctangent is the only one on the list, so a call to TRATST would be futile at this point.

2) The current point counter is incremented to the second point in the buffer and NOEND is called again. RATER does not need to recalculate yet; there is no endpoint across the next interval, which lies entirely in the buffer. Therefore, NOEND returns with x equal to 98, y at 547, and rate the same as before. The rate is not greater than that previously determined, so the saved

value is unchanged. TANGNT is called and adds the arctangent of the second segment (6.22) toTAN. TRNTST is now called; it returns the magnitude of the difference between the two arctangents, DIFFERENCE=.05. This difference is compared to TANDIF, which for this user drawing at rate 14 has a value of .19. The change in direction falls well below this value, so no start of corner is determined. STRAIN returns to 2), increments the current point counter, and continues.

3) This loop continues until point 7 is reached. The x- and y-coordinates of point 7 are -667 and 531, respectively. The arctangent of the segment between points 7 and 9 is .25. At point 8, however, the arctangent has changed to .62. Meanwhile, the rate has changed to 15, so the value of TANDIF is .20. Thus, when TRNTST returns a change of arctangent of .37, something happens.

4) The significant bend in the line indicates that the line is entering a corner. The current point counter is backed up one point, so that it points to the end of the first straight segment. The x- and y-coordinates of this point are stored in THOLD, and a pointer to this data is stored in the second element of CORNER. The current point counter then goes into DATP.

5) A call is made to subroutine LINE, which calculates the slope of the line segment defined by the points indicated by the first two elements in CORNER. This information will be of use later, so the slope is stored in the third element of CORNER.

The maximum rate reached across the segment (15) is stored in a location called RMAX1.

Because of a tendency to make rounded, rather than sharp, corners when sketching, it can not be assumed that a corner occurs at a single point in the original sketch. To cope with this problem, STRAIN searches for the straight line segments on either side fo the corner. Using these segments, then, the algebraic intersection of these lines is calculated, and this intersection is edfinde to be the corner connecting the two segments.

6) This method for calculating corners renders the data between line segments valueless. The collection of points which make up the corner in the raw data are useful only where they help to define where the second segment begins. Just as the corner was defined to begin where the change in arctangent was greater than TANDIF, the corner is defined to end and a new segment to begin where the delta arctangent falls below this limit. Thus, once the start of the corner is found, a new cycle of calling NOEND, TANGNT, and TRNTST is begun. Because the current point counter was backed up one point, the first results of the first cycle are the same as those described in 5) above. Since .37 is greater than TANDIF, the corner is continued. The next cycle, on point 9 results in an arctangent of 1.06. The difference between this value and the arctangent of the previous segment is .44, which is still greater than TANDIF.

7) This cycle is repeated until between points 10 and 11 the difference in arctangents has fallen to .13. This small change in direction indicates that a new segment has started.

8) The current point counter is backed up one point to get it to the first point in the segment (since the difference in arctangents was small, the segment must have started with the previous point). This point is preserved in THOLD and CORNER. CORNER is examined to see if it contains information about two segments, so the corner between the segments can be calculated. In fact, only one segment has been found and the starting point of a second one. Since no calculation can be made until the second segment is found, STRAIN returns to 2) to search for it, saving the data in the appropriate locations in CORNER and THOLD.

TABLE A

DATP	CORNER	THOLD	
		x	y
1	->	194	540
7	->	-687	531
-	1	-	-
11	->	-743	431
20	->	-727	-791
-	-4668	-	-
23	->	-719	-745

By the time the routine gets back to 8), the current point counter has made its way up to 23, and a second corner has been delimited. DATP, CORNER, and THOLD have the values shown in Table A.

There are now two segments, so their intersection can be calculated. An examination of Table A shows that one would expect the corner to fall between -687 and -743 in the x-direction, and between 531 and 431 in the y-direction--approximately. Once this intersection has been determined, the exact endpoints of the first line segment in the sketch are known, and may be saved. Therefore, let us digress from the original sketch and see how this step is performed.
9) First, the angle between the two segments defined in CORNER is checked to see if it is very small, in subroutine CFSA (Check For Small Angles). For very tight angles, such as occur in overtracing, the precision of the arithmetic permitted by the computer was found to be inadequate. The calculated intersections of lines at small angles were frequently found to be highly inaccurate. As a result of this difficuly, the actual raw data was deemed preferable to calculated data for determining corners at small angles. Calls to EXTRMR from NOEND have previously determined if any extremes exist along the line so far. CFSA first determines the arctangents of the two segments defined in CORNER, then checks the difference between these arctangents to see if the two segments qualify. It then looks to

see if there are any extremes. If so, the point of interest must have an associated point number which falls somewhere between the indices of the midpoints of the two segments in CORNER. The "average" point numbers of the two segments are calculated, therefore, and the list of extremes is searched for one with an index which falls between these values. If one is found, and if the angle between the segments is small enough, then CFSA returns the x- and y-coordinates of these extremes as the location of the corner between the two segments. Parenthetically, if no such extreme is found, but the angle is still small, then the value returned is the second end of the first segment. If the angle is not small, then CFSA just does a little house-cleaning, discarding extremes already passed, and returns.

In the case of the sample sketch, while an extreme was found, the angle between the segments is nearly ninety degrees. This angle is too large to be considered, so CFSA returns no value.

10) The corner must be calculated, a task performed by CFIX. Since two points on each of two line segments in CORNER are known, the formulas for each of the lines (Y=A*X+B) can be calculated. "A" for each line is the slope, calculated by LINE, contained in slot 3 and slot 6 of CORNER for the first and second lines respectively. "B" can be determined by: B=Y-A*X1. This equasion can be calculated by taking either of the known points in CORNER, getting its x- and y-coordinates, and substituting. Once the formulas for the two segments are known, another fact

can be applied--at the intersection, X1=X2 and Y1=Y2. Therefore:

$$A1*X+B1=A2*X+B2$$

and:

$$X(\text{intersection})= \frac{B2-B1}{A1-A2}$$

Once X(intersection) is known, it can be substituted into the formulas for either of the lines to determine Y(intersection). In the interest of accuracy, in fact, X(intersection) is substituted into both formulas, and the resulting Y which causes the least change in arctangent from those of the two segments in CORNER (there is bound to be some slight adjustment) is used as Y(intersection).

The above description is true in most cases. However, there is a special case which arises when one of the lines is nearly vertical, as is the case in the second line segment of the sample sketch. When a line becomes vertical, its slope becomes infinite. Dealing with infinite, or large, numbers in a computer becomes difficult, since one begins to encounter round-off and overflow difficulties. There is one saving grace, however. A line is vertical because there is only a small variation in its x-coordinate across its length. In this case, there can be little error in assuming that the x-coordinate of the

intersection is the same as the x-coordinate of the point of the vertical line segment nearer the proposed corner (in the case of the sample sketch, the x-coordinate of point 11, x=-743). This value can then be substituted into the formula for the other line in CORNER, to determine the y-coordinate of the intersection. This approach is the one which CFIX takes, returning the values X(intersection)=-743, Y(intersection)=530. If both lines are nearly vertical, then the discovery of an implied corner was a mistake. The two segments are merged into one, and the program returns to look for a second segment.

11) Since both ends of the first segment have been determined, the first segment can be saved by a call to LINER. The data about straight line segments is stored in a variably sized structure; a more complete description of the data structure can be found in Appendix I. Generally, the data which is stored about the endpoints is as follows: the x- and y-coordinates of the two endpoints of the line segment; the index of the position in the raw data where the point was first discovered (the first point in the stroke, or the beginning point of a corner); and a flag indicating whether the point was immediately preceeded or followed by a pen-lift flag. The line is stored as a relation between the two endpoints, holding information about the maximum rate and pressure attained while the line was drawn. Absence of such a relation means that no line was discovered between two points. A point can have as many line relations associated with it as necessary to represent the picture, but in the current

approach, a point can have either one or two lines related to it after the initial pass at finding straight lines. On the segment just discovered, the first point will have a single associated relation, one with the second point. The second point, being a corner, is related to the first point (the same relation, in fact), and eventually to a third point which will define the second corner discovered. Since no latching is done at this pass, there can be no more than two lines associated with a point.

12) Once the segment has been saved, it can be discarded from CORNER, THOLD, and DATP. The beginning point of the second segment is shifted to the first position in CORNER, and the remaining data is shifted down accordingly in the various arrays. Then the pointer in CORNER to the first point in THOLD is changed to point to the second point just saved by LINE. This second point will be used instead of the numbers in THOLD as one end of the next segment defined, the next time LINE is called. The common endpoint will thus be defined.

The state of the program has now returned to where it was after the first corner was discovered. The only difference is in the data in the various arrays (see Table B).

TABLE B

DATP	CORNER	THOLD	
		x	y
11	->POINT(2)		
20	->	-727	-751
-	-4568	-	-
23	->	-719	-745

As it did before, therefore, STRAIN loops back to 2) and continues. The second corner is determined, and because the rate slowed toward the end of the line, the third turn in the line is broken into several corners. STRAIN has now gotten to point 84 looking for a corner to end, so it can go to determine the seventh segment. When it picks up point 84 in a call to NOEND, however, it is discovered that the data element is a pen up flag; the line has ended. Since there are no more corners to be found on this line, the program branches to ENDSEG, which deals with end conditions of lines.

13) ENDSEG basicallly deals with the end of a line the same way the beginning of the line was handled in 1). Since the last point in the line obviously ends a line segment, the current point counter is backed up one before the pen-up flag. A pointer to this point is placed in CORNER, and its index is saved in

DATP, along with the pen lift flag (Note that since this point will be disposed of immediately, there is no need to save its coordinates in THOLD. There is no danger of the data being overlaid by a refill of the buffer). LINE is called to figure the slope. Two segments have been determined thus, so the corner between them can be calculated by a call to CFSA or CFIX. Then the first segment can be saved by LINER.

14) Finally, since the end point of the stroke is known exactly, from the data, no calculation needs to be done to determine the last point of the last segment. It can be saved directily by LINER. Once this operation has been done, all the information which can be determined directly from the stroke has been dealt with. CORNER is cleared, and STRAIN returns to 1) to look for more data.

There are two other possible cases which might have to be dealt with by ENDSEG, however. One is that the beginning of a corner has been found, but the curve of the corner has not terminated at the point where the pen lift flag is encountered, as is the case in the sample sketch. In this instance, there is little choice but to ignore the data occuring after the corner began. There is no way to calculate a position for this final corner, so it is simply dropped. This rarely results in any major distortion of the sketch, but occasionally, an entire final line is dropped if the line is sufficiently curved to fool the program (See the discussion on curves, in Section II). The calculation for this

case is essentially the same as in 13). The second case, which occurs more frequently, is that of a single straight line segment. If the pen is lifted before any corner is drawn, ENDSEG has no interim corner to find. In this case (i.e. CORNER only has two or three cells filled in), LFSA and CFIX are not needed, and the two points (first and last on the stroke) can be saved directly by LINER. In either case, all the information which can be found on the stroke is done with and CORNER is cleared.

When STRAIN returns to 1) to pick up another line, it discovers that there is no more data; it is done. The completely STRAINed sketch appears in Figure 16. The data is stored in a structure of points and lines described in Appendix I, and is accessible to other programs for further analysis. The above description covers essentially all the steps required to create this structure, covering all the special cases. The only likely extension is that which will enable the system to recognize and describe curves.



IV. FUTURE

Where Do We Go from Here?

DESCRIPTION OF A SKETCH

Having examined all that has occurred since HUNCH was begun, let us go back a bit to look at the original goals, particularly, the development of a hierarchical description of the sketch. The output of the straightening pass at the data is a two level structure of lines and points. While this structure makes the data much more manageable, it is not much of a step toward a description of the sketch in any normal human sense.

To elucidate what is meant by "a normal human description," let us try to generate one from a particular sketch. Figure 17 is a sketch of a house plan, much simplified. A verbal description which one might expect from a human is as follows:

1. It has 5 rooms
2. Rooms 1 and 6 have access to the outside; room 6 through one door, room 1 through two.
3. All the rooms are rectanglular, having four walls, except rooms 3 and 6 which have six walls each.
4. Room 1 is connected to the outside through (doors in) its left and right walls, and to room 2 through its bottom wall.



Figure 17a.



Figure 17b.

5. Room 2 has access to room 1 through its top wall, and to rooms 3 and 4 through its bottom wall.
6. Room 3 is connected to room 2 through its top wall, and to rooms 4 and 5 through two doors and one door, respectively, in its bottom wall.
And so forth.
This verbal description is not complete. One might wish to describe the exact configuration of rooms 3 and 5, to enumerate which walls were on the perimeter of the building and which walls were shared by the various rooms. The verbal description does not even specify a unique house plan. However, it does supply sufficient information such that some specific questions could be asked about the relationships between the rooms ("What rooms would I cross going from room 1 to room 5?"), about the overall accounting for the building ("How many rooms? doors?"), and about specific parts of the sketch ("How big is room 3?"). (Note that while the last question is not specifically answerable from the description, the area which has to be examined to determine the answer is considerably restricted.

In order to generate such a description, a person (or program) needs to know what kinds of elements might be found in a sketch, what kinds of questions are going to be asked about these elements, and how to recognize the various elements represented in the sketch. In the sample sketch, there are basically three elements: walls, doors, and rooms. The kinds of questions one

might be asked are about position, relative size, and relationships between elements. If the information is stored in some reasonably structured way, these questions ought to be easy to answer, once the various elements have been found.

The recognition of elements is perhaps the most difficult requirement. In the sample sketch, three different representations were used for doors (Figure 17b). In this simple case, then, what are some of the cues people use to identify the three elements which comprise the sample sketch?

To find the rooms in a plan, one would look for areas enclosed by sets of lines which define walls and which do not enclose other rooms.

Walls are characterized by sets of fairly long colinear, continuous lines which appear at the edges of areas which are rooms. They may have doors in them. They comprise most of the lines in a plan sketch.

Doors may be characterized by the fact that they appear in walls. They may be represented by a break in an otherwise colinear wall or a set of (probably) short lines bracketing a break in the perimeter of a room. These short lines will probably be perpendicular to the lines which make up the wall in which the break occurs. Finally, there may be a line about the same length as the break in the wall which lies at a small angle

to the wall in which the break occurs, and which shares a common end point with those points making up one end of the break.

The seeming circularity of some of the definitions (a wall is an edge of a room, and a room is limited by its walls) is an asset of such a description. One can apply one rule tentatively (take a guess at a room, for example), and then use the consequence of this guess to draw other conclusions. Eventually, one will either come to a solution, or because of the circularity of definition, one will arrive at a contradiction. If the description were completely directed and acyclic, one could drift farther and farther from the facts after an erroneous guess without ever noticing that anything was wrong.

In order to have a computer program which can construct a descriptive structure for a particular class of sketches, then, one must be able to specify to the program what features to look for and how the program is to go about recognizing these features. The process of recognizing features seems to require the application of those functions already discredited in earlier discussion: latching, horizontalizing, verticalizing, parallelizing, perpendicularizing, conlinearizing, normalizing, and continuing. While this is true, in this case the functions are applied in some context. Earlier attempts were simply exercises in investigating how the HUNCH approach could be applied to solving these various functions. The result was a

program which knew a rule and which applied that rule under all conditions. The effect of this method was that the rule was appllied under conditions where it was possible but not appropriate. In the proposed solution, the program would have some idea about when the rule could reasonably be applied while searching for a specific item.

Using this system, the user would name a set of features which would be searched for in a particular class of sketches. The names of these features will provide the means of describing the sketch, and relationships between the features will provide clues to the hierarchy for the description (a kind of precedence relation). Once the features have been named, the user would describe the attributes of each feature which would be searched for in a given sketch. In general, a feature consists of a set of points, or lines, or perhaps other features, or a combination of these elements. Identifying whether a part of a sketch is a particular feature involves matching elements of the sketch to attributes of the set describing that feature. For example, an attribute of a one element set consisting of a straight line segment is the direction in which the segment lies; another attribute is the length of the segment. The process of telling the program how to recognize a particular class of sketch involves naming a set of features and then describing attributes of the sets which determine a feature. This description will provide a structure against which sets of lines and features will be matched by the program providing the description of the sketch.

EXISTING KNOWN SETS

After a sketch has been processed by STRAIN, the output of the operation can be considered to be two sets: a set of lines and a set of points. These two sets are the primitive sets from which the rest of the description will be derived. Furthermore, the elements of these sets each have their own set of primitive attributes.

The most basic element of a sketch is a point. It has two primitive attributes: position and sequence. The initial value of position is the obvious one--simply, where in the coordinates of the tablet the point lies. Later analysis might require changing this value (a three-dimensional mapping, for example). Sequence can be taken to be the temporal position of the point. In the process of straightening the sketch, the index of a point, in the original steam of data, which is the start of a corner or an end of a stroke is saved and associated with that point in the straightened data structure. These two basic attributes, then, provide a one-to-one mapping from a point number into a three-dimensional space/time volume.

There is another attribute of a point which should be considered; that is, it can define one end of a line segment. In the straightened data structure, the role this attribute can play is fixed, since there are at most two line segments which can have a given point as an endpoint. This attribute was not

included in the discussion of primitive attributes, however, because in defining features, one might wish to construct lines not appearing in the original sketch. Thus the manifestation of this attribute might change under varying circumstances. More properly, this attribute of a point will be reserved for the discussion of the relationships between points.

A larger set of attributes is associated with a line segment. As with points, there are two obvious primitive attributes: direction and magnitude. The direction can initially be taken to be the arctangent of the line relative to the positive horizontal direction of the tablet. Its magnitude is its length, using the tablet coordinate system. As with the position of a point, the value of either of these attributes might have to be changed if the line is mapped into three-space. In the process of straightening, the fastest rate and the greatest pressure reached while drawing a particular line are associated in the structure with the line. These attributes suggest others which might be considered at some later date, if the means of input should be modified. One can imagine a line having width, color, texture, even thickness. Finally, as the inverse of the point attribute, two attributes of a line segment are the points which define its ends. Unlike the point example, the two endpoints of a segment are fixed, so these attributes are unchanging.

Given these two sets, some analysis of a sketch is possible, as

long as that analysis is related to some absolute scale. One might wish to examine all the lines longer than a certain minimum length, or those lying in a particular direction. The process of looking for horizontal and vertical lines requires just this sort of analysis. Most analysis requires the ability to distinguish relationships between sets of points or lines, however; there is no absolute background against which the measurement takes place. Because of this need, there must be the capability to describe relationships between points and lines which can be assigned as attributes to sets. These primitives are discussed in the next section.

LINE SET ATTRIBUTES

In describing the features of a sketch, one uses words like parallel, perpendicular, angle, corner, near, and so forth. It is proposed in this section to define a set of primitives which can be applied to lines to test them for these descriptors, and to describe how the procedures which establish the existence of these attributes might be implemented. Given these primitives (and some other, more general ones described in a later section), one can describe the attributes of a set of elements which would make up a feature of a sketch.

PARALLELISM: In most sketches, there are preferred directions. In the sketch of the house plan of the average house, the great

majority of the lines would fall into two perpendicular directions. In an axonometric sketch, there would be three preferred directions. A histogram of the direction of the lines in a sketch versus either the number of occurrences of a given direction, or the total length of line in a particular direction, or a combination of both, will show peaks at the various preferred directions with a fairly narrow standard deviation (Figure 18). It is a simple matter to divide th sketch into families of lines, using the valleys between the preferred directions as division guide-lines. One could user rate and pressure to influence the decision, as far as allowable deviation is concerned. Some sort of average direction could be used to define the family which was implied, and this identifier for the family could be associated with each line in the straightened data structure. A set of lines could be considered parallel, then, if they all belonged to the same family.



Figure 18.

COLINEARITY: Once the family of a line is determined, the family identifier can be used to calculate the x- or y-intercept of that line. The result of this calculation could also be associated with each line in the structure. It is likely that intercepts would tend to fall in groups as arctangents do. A set of lines could be said to be colinear, then, if the set had the attribute of parallelism, and if each element of the same, or nearly the same, x- or y-intercept. Again, the definition of near could be subject to rate and pressure data influence.

CONTINUITY: In the strictest sense, a set of lines can be defined to be continuous if the set is conlinear, and if there are no "breaks" in the line. More specifically, a line is unbroken if there is never a case where, scanning from left to rght (or from top to bottom), the right-most end of the line segment is encountered before the left-most end of another line segment is found, if there are still line segments to the right. Normally, one would wish to include instances of "near continuity," where the break in the line is small, in this definition of continuity. This modification of the definition is somewhat risky, since it is prone to the same difficulties encountered in earlier latching attempts. A way to get around this objection would be either never to apply the weak continuity rule until other analysis had failed to provide a satisfactory result, or to flag a weakly continuous set, such that later difficulties might be resolved with a minimum of searching for

the error. In any case, it should be noted that this form of latching is only applied in a fairly explicit set of circumstances: the distance is small, and the lines to be latched are colinear.

With the above primitives, one could make a generous stab at reducing the complexity of a heavily overtraced sketch. A "Meta-line" could be defined as a feature of the sketch having the attribute that each Meta-line in the sketch would consist of a set of continuous line segments. The endpoints of the Meta-line would be the left- and right-most points which were attributes of the lines making up the set (in some cases, the top- and bottom-most points would be used), and the deviation in the y-intercept of the lines in the set could be used to define a width for the Meta-line. Once this information had been determined, further analysis could proceed exclusively at the Meta-line level. It would not usually be the case, however, that an analysis would proceed in an exclusively bottom-up manner, as described above. The example does show how the attributes of a set might simply be related with fairly powerful results.
SEQUENCE: In the set of points, a point which ends a line segment must be preceeded immediately by the point which began the segment. Similarly, the following sequential point is either the end of a line eminating from the point in question, or it is the beginning of the next line to be started. At any rate, the straightened data structure contains the complete sequence in

which all the lines in the sketch were drawn. Two lines are in sequence, then, if the second point in one line is either the first point in the other one, or it immediately preceeds the first point in the second line--or vice versa. A Dashed-line could be defined as a set of lines which are colinear, non-continuous, and in sequence.

ANGULARITY: The intersection of two lines forms an angle. Angles seem to perform two functions in a sketch: they permit definition of relationships between non-parallel lines ("line A is perpendicular to line B"), and they indicate intended changes of direction (as at corners). An angle provides a relationship between two (sets of) lines, and it consists of two defining elements: a pair of lines or line sets and a magnitude. The position of the angle can be taken to be the point of intersection of the two lines. The magnitude of the angle between line A and line B can be taken to be that solution of the following two equasinons which is non-negative and less than PI:
Magintude=B.direction-A.direction or
Maginiude=PI+B.direction-A.direction
Note that this method of measureing the magnitude makes the value of the result depend on which line is mentioned first; Angle.Magnitude(lineA,lineB) = PI - Angle.Magnitude(lineB,lineA). Since an angle has two sides, this distinction is important. To compare the magnitudes of two angles, he must first be certain that he is measuring the angles from the same side.

Where the corner between two lines exists, this definition of an angle is fairly simple to handle. In those cases where two lines do not physically intersect, however, the problem becomes more complex. One would like to create a point for the intersection, and then construct lines from it to the ends of the two lines whose angle is to be measured ("Construct point P, such that line(P,B) is colinear with line(A,B) and line(P,D) is colinear with line(C,D). . ."). This desire leads to the need for the ability to describe a "working point" and a "working line." Two functions are needed to modify the point-line structure: the first, P=Setpoint(X,Y), adds a point to the structure at location (X,Y) on the tablet (or perhaps some modification of the above to allow for three-dimensional positioning). The arguments of the function would serve to establish the position attribute of the element. Since the point did not appear in the original data, it has no sequence attribute. A pointer to this new point would be returned in P. The second function is L=Line(A,B); it constructs a line between points A and B and assigns L a pointer to it. The direction and length attributes can be calculated, while other attributes (rate, pressure, and so forth) are undefined. Once a point or a line has been created, it can be taken as an element in any set defined by the attributes described above. Thus, one might examine a sequence of points to see if they were colinear by constructing lines between them and then examining the lines. Similarly, the distance between two parallel lines segments could be found by constructing a line perpendicular to the lines from

one of the endpoints of the lines. By adding to the structure the intersection point of this line with the other of the parallel lines, the length of the constructed segment is determined. The value of this length is the distance between the two lines.

OTHER KNOWN SETS

While experimenting with primitives to describe features, one keeps arriving at a need to define a set with an attribute of area. For example, in the house plan, a room is an area enclosed by walls. Similarly, in an axonometric sketch, a surface of a solid can be described as an area enclosed by edges. It seems necessary, then, to define an extension to the current structure for a set of areas.

The attributes of an area are similar to those of a line. Corresponding to the line's attribute of length is the area's attribute of magnitude--the amount of area encompassed. This attribute can be defined by the number of tablet coordinate squares enclosed by the area. Corresponding to the endpoints associated with a line is the perimeter of the area. Unlike the endpoint attribute, which has a fixed number of elements, the perimeter of an area consists of an indefinite number of elements; it is a variable length list of pointers to features in the sketch which defines the set of elements containing the area.

Note that the set of elements defining the perimeter might change as the analysis of the sketch proceeds. The perimeter of an area might initially consist of a set of line segments. As these segments are absorbed into the description of features of the sketch, these features would be substituted for the lines. Thus, when the lines defining the room in a house plan are included in the description of the walls in the plan, the walls become the defining elements of the room. With the perimeter attribute of an area, however, it seems reasonable to extend the attributes of a line to include the attribute that a line is an element of the perimeter of an area, just as a point was described as one end of a line segment.

Other attributes which might be associated with an area are reflected in those of a line. An area could have an attribute of orientation, which would be defined as the direction perpendicular to the plane in which the area lies. Initially, the orientation of all areas would be the same--perpendicular to the plane of the tablet. In the case of a sketch of a three-dimensional object, however, this orientation might change (as might the magnitude attribute). While an area does not have either the attributes of rate or pressure, it could have color, texture, or thickness.

Having gone this far, it seems reasonable to propose that a further extension to the structure be added to permit the

definition of volumes. Just as the description of features in two dimensions led to the necessity of describing areas, it is inevitable that the need for descriptions of volumes will arise. Like areas, a volume would have the attributes of magnitude and perimeter, although the perimeter would consist of a set of areas. Orientation does not seem to be relevant in the description of a volume, but color and texture seem possible, along with density, center of mass, opacity, and just about anything else.

FEATURES AND SET ATTRIBUTES

Features may be defined by enumerating the attributes which must hold for elements of the set comprising the feature. Some of these features may be defined in terms of those attributes already described, as the Meta-line was defined. There are other attributes which will prove useful, however, which operate on sets in general, rather than on the specialized set described above.

BOOLEAN OPERATORS: The three operators AND, OR, and NOT specifically, may be used either as modifiers to attributes or as operators on sets. As an attribute modifier, the operators can specify that a particular condition may NOT occur, that either of two conditions may hold, or that a pair of attributes must hold

("colinear & ¬continuous V ¬colinear. . ."). As a set operator, the booleans would act as the Union, Intersection, and Set-Subtraction operators, permitting the concatenation of sets and the subsetting of sets (Wall::=wall & Door V Wall & Wall. . .). The effect of such an operation on the description structure would be the addition of an element with links down to those elements being concatenated (or in the case of a subtraction, the creation of two elements linked to the original set from below).

NUMBER: A set may have to have a particular number of elements (or features). There must be a means of specifying that number, then, and of comparing a number of elements against that number. A rectangle, for example, implies an area with four edges in its perimeter set. Once an area has been isolated, the number of its edges must be compared to the number of edges specified for the set, to see if it is less than, equal to or greater than the required number.

Similarly, since some attributes return values other than boolean values, the relative magnitude of these values should be comparable, addable, subtractable, and so forth. This requirement implies that either numbers of elements or value of attributes must be countable and able to be operated on by the normal arithmetic functions.

SIMILARITY/EQUALITY: Two sets are equal if all the attributes

of both sets and of all the elements of each set are equal. Two sets are similar if the values of the specified attributes are the same. In the absence of an attribute, a particular feature is similar to a feature name if it is in that feature class. Thus:

rect1==rect2 if everything is the same.
rect1<=>rect2 if rect1.width=rect2.width &
rect1.length=rect2.length
rect1<=>Rectangle if rect1 is in the class of features called Rectangle.

These working definitions permit the comparison of sets by permitting the user to define what he means by two sets being similar. In a case where it is desirable to define features which are similar but which may have minor variations, this ability can greatly simplify the definition process.

MEMBERSHIP: A particular element has the property that it either does or does not belong to a particular set. In the hierarchical description, if an element belongs to a set, there will be a vertical path from that element linking it to the set name (Wall e Area.Perimeter).

RECURSE

In order to demonstrate how the functions defined above might operate, the features mentioned in describing the sketch at the beginning of this section will be defined in terms of these functions. The sketch had basically three features: Rooms, Walls, and Doors. The third paragraph on page 72 gives a verbal description of what a person might look for in recognizing these features. Table C gives a translation of this description into the set of attributes defined in this section. In order to complete this definition, three auxiliary features were defined: Breaks, Clusters, and Metalines. The description of a door mentioned that it was indicated by a break in a wall. This description implies that what is meant by a break is known, so it has to be defined as a feature as well. The other two features are defined merely to help simplify the descriptions. A meta line is defined formally in the same way it was described earlier in the text. A cluster is simply a collection of points no farther distant from one another than some distance, whose magnitude is defined by the rates of the lines which the points define.

The notation used to define the features is a sort of bastardized set notation. A glossary of the notation is given in Table D. While the circularity of the definitions for Door indicates that more work is desirable to make this method of

describing features more humane, it does show that such a method is a viable approach to the problem. This statement is reenforced by the fact that I had no idea about how the formal definition was going to be implemented until after I had defined all the sets described in this section. Since I was able to do the formal definition using only those sets, it can be argued that they are at least sufficient to accomplish the job at hand.

TABLE C

```
Room::=R | R<=>Area & ( ^R1 | R1<=>Room & (R &^ R1)^== R)

        *A room is an area which contains no other rooms

Room.Perimeter<=>R.Perimeter


Wall::=W | W<=>Metaline

    V Door

    V W1 & W2 | W1<=>Wall & W2<=>Wall & W1^==W2
          & L1 e W1 & L2 e W2 & {L1,L2}.Continuous

        *A wall is the concatenation of two continuous walls

    V W | R<=>Room & W e Room.Perimeter


Metaline::=S | S=={L | L<=>Line} & S.Continuous

Metaline.Direction<=>L.Direction

Metaline.Endpoint=={P1,P2} | L1 e S & L2 e S
        & P1 e L1.Endpoint & P2 e L2.Endpoint
        & (^L3 | L3 e S & P1 e L3.Endpoint
             & P1.X < P3.X & P2.X > P3.X)

        *The endpoints of a Metaline are those with the Maximum
             and Minimum X-coordinates

Metaline.Length<=>line(P1,P2).length


Cluster::=C | C=={P | P<=>Point} & P1 e C & P2 e C
    & L1 | P1 e L1.Endpoint & L2 | P2 e L2.Endpoint
    & L=Line(P1,P2) & L.Magnitude < F(L1.Rate,L2.Rate)

        *A cluster is a set of points such that the length of a line
             between any two points in the set is less than some
             function of the rates of the lines of which those two
             points are endpoints
```

(Table C, continued)

```
Break::=B | B=={C1,C2 | C1<=>Cluster & C2<=>Cluster & C1^==C2

    & (¬L | L<=>Line & L.Endpoint e C1 & L.Endpoint e C2)

    & (¬C3 | C3<=>Cluster & P1 e C1 & P2 e C2 & P3 e C3
        & L1=Line(P1,P2) & L2=Line(P1,P3) & L3=Line(P2,P3)
        & {L1,L2,L3}.Colinear
        & L1.Magnitude > L2.Magnitude
        & L1.Magnitude => L3.Magnitude)

         *A break is a set of two clusters with no line having
              one endpoint in each cluster, and with no cluster
              lying between the two clusters

Break.Direction<=>L1.Direction


Door::=D | D=={C1,C2 |
     (C1<=>Cluster & (P | P e C1 & P e L1.Endpoint
                | L1 e W & W<=>Wall)
          & C2<=>Cluster & (P | P e C2 & P e L2.Endpoint | L2 e W & W<=>W

          & {C1.C2}<=>Break

          & {L1,L2}.Colinear)

         *A door is a pair of clusters which have as elements the
              endpoints of a pair of colinear walls surrounding
              a break

     V ((S1 | S1<=>Metline) & (S2 | S2<=>Metaline)
              & {S1,S2}.Parallel
         & C1<=>Cluster
         & C2<=>Cluster
         & {C1,C2}<=>Break
         & P1 | P1 e S1.Endpoint & P1 e C1
         & P2 | P2 e S2.Endpoint & P2 e C2
         & Line(P1,P2) e R.Perimeter | R<=>Room
         & D.Direction-S1.Direction= +-Pi/2  }

         *or a pair of clusters forming a break which are endpoints
              of a pair of parallel metalines such that a line
              connecting the endpoints is on the perimeter of a
              room and perpendicular to the direction of the
              metalines
```

(Table C, continued)

```
V Dl | Dl=={D,L | D<=>Door & L<=>Metaline
    & C1 e I & C2 e D
    & P | P e L.Endpoint & (P e C1 V P e C2)
    & L.Direction-Door.Direction < Pi/4}
```

*or a door with a line projecting from one of its clusters at an angle less than 45 degrees

Door.Direction<=>Break.Direction

TABLE D

Symbol	Meaning
::=	
::=	is defined to be
{. . .}	is the set
|	such that
V	or
&	and
¬	not
e	is an element of the set
xxx.yyy	the attribute yyy of set xxx is true
==	the set is equal to
<=>	the set is similar to
(. . .)	group delimiters (to aid in reading this stuff)

REFERENCES

Ellias, T.O., J.F. Heafner, and W.L. Sibley, THE GRAIL PROJECT: AN EXPERIMENT IN MAN-MACHINE COMMUNICATION, The Rand Corporation, Memorandum RM-5999-ARPA, September, 1969.

Negroponte, Nicholas P., THE ARCHITECTURE MACHINE, MIT Press, 1970.

_____, MACHINE RECOGNITION AND INFERENCE MAKING IN COMPUTER AIDS TO ARCHITECTURE, Proposal to the National Science Foundation, 1973.

_____, and James Taggart, "HUNCH--An Experiment in Sketch Recognition," EIRA PROCEEDINGS, edited by William Mitchel, January 1972.
(also in COMPUTER GRAPHICS, edited by W. Giloi, Berlin, 1971).

Saderholm, B.V., "Paper 'Keyboard' Runs Experimental IBM System," IBM Release #C3-030873, Yorktown Heights, New York, March, 1973.

Sutherland, I.E, "Sketchpad: A Man-Machine Graphical Communications System," AFIPS Proceedings, 1963.

Appendix I

EXISTING DATA STRUCTURE

Appendix I is reprinted from
MACHINE RECOGNITION AND INFERENCE
MAKING IN COMPUTER AIDS TO
ARCHITECTURE

EXISTING DATA STRUCTURE

In any complex system, it usually becomes true sooner or later that there is a demand for a data structure with a varying number of elements of varying size. The data structures available from Fortran are inadequate. Consequently, the General Purpose Structure was developed for users of the operating system. The structure is created and modified by a set of function calls which can be made from Fortran to the system. These permit creation and deletion of structures, and they permit the addition, subtraction, modification and accessing of data elements in the structure. The structure is created in free storage made available by supervisor calls to the operating system, and, therefore, is limited in size only by the physical size of the memory of the machine in which it resides.

The structure has three constituent elements: a Structure Pointer Block, a set of points, and a set of links. They are related in a somewhat hierarchial fashion. Since there may be more than one structure in the system being accessed at a given time, they are separately identified by a Structure Pointer Block. Each Block consists of six data elements containing information about the particular structure: a pointer to the first point of the structure; a count of the number of points in the initial point block of the structure; a flag indicating if any points have been dropped; the size of a link, or zero, if link size is not fixed; the virtual point number of the last point created; and a pointer to the next Structure Pointer Block available in the system, if there is one.

Points are currently allocated in blocks of seven at a time, in order to increase the ease with which they are manipulated. Each point consists of four data items, two of which may be accessed by the user as general purpose arguments. (Typically, they are used as the x- and y-coordinates of a point in a display of some sort. Extending the number of arguments from two to some higher number is a simple extension being contemplated.) The other two arguments are a pointer to the first link associated with the point, and the point's number. As points are created, they are assigned a point number, sequentially from one for the first point created. In order to avoid confusion as more points are added and deleted, this number is fixed. Thus, even though a slot in a point allocation block may be reused, the numbers of the points on either side of it do not change, and the numbers of new points as they are created are monotonically increasing. The virtual point number of any newly created point wil be one more than the number of the last point created as indicated by the Structure Pointer Block, and the Block will be modified accordingly.

A link is a means of establishing a relation between two points. A request to add a link between two points appends a copy of the link requested to the link chain pointed to by the third data field in a point. A link consists of at least two fields: a pointer to the point being linked to, and a pointer to the next link on the chain. The size of the links in a structure may be constant or varying. If at creation time, the structure is declared to have uniform links, the size of a link is stored in the Structure Block Pointer, and that size is used throughout. Otherwise, the size of a link is declared at the time the link is created and stored in a field of the link itself. Links may have between four and sixty addressable fields. A field is four bits wide (and thus may contain a number beetween 0 and 15), and fields may be addressed singly or in groups of up to four (generating a sixteen bit wide field). The first four fields in a link are used for the pointer to the point linked to. The next four are for the next link pointer, but they are not addressable. The next field contains the link size if it is non-uniform. The remaining fields are free to be used for storage of any information about the relationship between the two points desired.

In order to create a structure, the

user makes a function call of the form: PTR=CONSTR(size) where size is the size of the links in the structure if uniform, or zero if varying. CONSTR sets up a Structure Pointer Block, allocates space for the first seven points, and returns to PTR the address of the Structure Pointer Block created. All further calls referencing this structure take this pointer as their first argument. Since any call with an improper Structure Pointer Block specified can only lead to disaster, the other calls check to see whether the address handed in future argument list points to a valid Block (hence the pointer as the last element in a Block). An invalid block causes the system to type out an error message and halt. This is the only fatal error. Other errors, if they occur, are returned as results from the function, and a message is printed on an output device available to the user consisting of a two letter code. The first letter specifies in which function the error occurred, and the second letter specifies what the error was. Most errors are caused by faulty argument passing, either by requesting an impossible change or asking for information from non-existant links. In the case where a change is requested, if an error is detected, the change does not occur. In some instances the returned error code can be useful in programming. For instance, since links can be referred to by sequential number, in order to access every link associated with a given point, a counter specifying the number of the link to be accessed could be increased by one until an error returns saying there is no such link. Then the program knows it has finished. Similarly, to establish if a link between two points exists, any reference to that link specified by those two points will return an error code if no such link exists.

Other function calls are as follows:

Function Calls

To add a point to the structure
PN=PADD(PTR,VALUE,VALUE1)
returns the virtual point number of the point added or -1 if there was an error. Since each point can have two arguments associated with it directly, they are set by VALUE & VALUE1. The error code is Pn.

To add a link to the structure
x=LADD(PTR,PN,PN1,SIZE)
PN & PN1 specify the points between which the link is to be added. SIZE specifies the number of fields in the link (required whether or not the SIZE is uniform). The error code is Ln.

To access or modify an argument in a point
x=GPOINT(PTR,PN,ARGN,VALUE)
sets VALUE equal to the contents of ARGN of point PN. The error code is Hn.

To access or modify a set of fields in a link
x=GPFLDR(PTR,PN,LN,NO,WIDTH,VALUE)
x=PPFLDR(PTR,PN,PN1,NO,WIDTH,VALUE)
returns in VALUE the contents of the specified field(s) in the link specified by PN,LN or the link between points PN,PN1. Note that the difference between the two calls is simply that GPFLDR specifies a link by link number while PPFLDR specifies a link by passing the two points the link connects. The error code is Kn.

x=GPFLDF(PTR,PN,LN,NO,WIDTH,VALUE)
x=PPFLDF(PTR,PN,PN1,NO,WIDTH,VALUE)
puts VALUE truncated to the size specified by WIDTH into the specified field. The difference between the two calls is the same as above. The error code is Fn.

To delete a link from the structure
x=LDROP(PTR,PN,LN)
x=LLDROP(PTR,PN,PN1)
removes the specified link. The error code is En.

To delete a point from the structure
x=PDROP(PTR,PN,[COLLECT])
drops the specified point from the structure ONLY if the point has no remaining links. If COLLECT is requested, points are garbage collected after every 8 drops. The error code is Dn.

Appendix II

THE GRID FACILITIES

Appendix II is reprinted from
MACHINE RECOGNITION AND INFERENCE
MAKING IN COMPUTER AIDS TO
ARCHITECTURE

DISK GRID PACKAGE

The grid package provides the FORTRAN user with a set of x-y addressable grids (up to 1024 by 1024 bits) which are used to store sketches and more generally, data from a number of graphics input terminals including the Sylvania Data Tablet for drawings made by hand and a television camera for input of predrawn sketches. This type of storage medium allows a sketch to become completely independent of time and provides a computer scratch pad for analysis of complex configurations.

Each grid is stored as a bit map on a fixed head disk storage device, with each 1024 point line represented by a 128 byte record. A grid can consist of between 1 and 1024 such lines, and any number of separate grids may be used, limited only by the capacity of the disk. When a 1024 by 1024 grid is used to represent a sketch drawn with the Sylvania Tablet, which addresses 4096 by 4096 points, a bit is set on the grid if a line drawn on the tablet passed through a square 4 by 4 tablet coordinates in size. When used with the television camera, each line of video data is stored one after another until the entire sketch or drawing is scanned.

The data on the grid is accessed by means of an assembly language program which transfers a "window" of arbitrary width and height from the grid to a FORTRAN user's array in core. Likewise, data may be transfered from a FORTRAN array to the grid. In addition, a scale may be specified so that one element of the array can represent anything from one bit in the grid to the entire grid, with the value returned equal to the number of bits set within that portion of the specified window. At the largest scale, with the array containing the entire grid, most details are too small to affect the mapping into the array, leaving only the outlines of the major forms, as when the human eye views a scene from a distance. Since an image of the original sketch is now in core, the entire sketch can be examined very easily, in much less time than it would take to scan a magnetic tape containing the original positions. Based upon the shapes, voids, bodies, etc. found by scanning the array, a program can select areas of the sketch to be examined in greater detail. As the scale, hence the size of the window, is decreased, more and more details appear. Usually there is some scale, about 3 or 4, at which most of the important features are present but at which noise from minor movements of the pen is absent. Features of the sketch found at smaller scales are usually of no significance as far as position-dependent interpretations are concerned, since they are usually the kind of noise ignored by a human examining a drawing.

Data can be entered into a grid from a variety of sources, including magnetic tape, a vidicon camera, and directly from a FORTRAN program. The most common method takes its input from a magnetic tape or disk file produced by the DRAW program in HUNCH, consisting of a list of pen coordinates measured at constant intervals. These coordinates are converted to grid coordinates and the appropriate bits set on the disk. If two successive points are more than one grid unit apart, as often happens with lines drawn at high velocity, the intervening points are interpolated, so that the bit image on the disk approximates the appearance of the completed sketch. Thus the programmer need not burden himself with the problem of connecting points, which would be very difficult in the time-independent context of the grid. Since most drawings are smaller than the maximum size of the grid, the conversion program automatically reduces the size of the grid to the size of the sketch, saving both disk space and access time. Another input source is a television camera which enables the grid to replicate a completed paper sketch. Data conversion in this case is very simple, as the vidicon scans line by line, just as the grid is organized on the disk. It is also possible to set bits in the grid directly from a FORTRAN program, by means of an assembly language routine which maps a FORTRAN array onto the disk, in a manner analogous to the





window program described above. Finally, there is a complete set of entry points which enable the assembly language programmer to set and retrieve single bits and to access individual lines in the grid.

Following are examples of 5 of the more important of the 15 FORTRAN callable entry points in the grid package.









Subroutine DISPLW

Purpose

The purpose of the subroutine is to display the contents of an array on the ARDS.

Usage

```
INTEGER*2 ARRAY(XDIM,YDIM), DENSTY, SDIM, YLIM, GRIDF, DISPF

CALL DISPLW(ARRAY, DENSTY, XDIM, YDIM, GRIDF, DISPF)
```

The subroutine draws a grid XDIM by YDIM and fills in those squares whose corresponding array elements are not equal to zero.

ARRAY — is the array.

DENSTY — is the number of fill-in lines to be drawn per square. Optional default is 4.

XDIM, YDIM — describe the array. Both are optional. XDIM defaults to 32. YDIM defaults to XDIM.

GRIDF — specifies if the grid is to be drawn.
= 0 no grid
= 1 grid (the default)

DISPF — allows the grid to be drawn without filling in the squares.
= 0 no fill in display
= 1 fill in (the default)
= -1 fill in with the number of hits

Subroutine GRDSK

Purpose

The purpose of the subroutine GRDSK is to convert a drawing from time-dependent magnetic tape to position-dependent disk.

Usage

```
CALL GRDSK(IDISPL,ICNVRT,IERASE,GCB)
```

All arguments are optional, if omitted, the default is assumed.

If IDISPL = 0 drawing will not be displayed (default).
= 1 drawing will be displayed as it is converted.

If ICNVRT = 0 no conversion will take place.
= 1 conversion will take place (default).

The ICNVRT option allows the displaying to original drawing from tape.

If IERASE = 0 the drawing will be placed on the grid along with any previous drawing.
= 1 any previous drawing will be erased (default is to the value of ICNVRT)

GCB is the Grid Control Block (see INIGRD)

```
DIMENSION ARRAY (XDIM, YDIM)

CALL WWWDOW(ARRAY, SCALE, XBIAS, YBIAS, IERR, DRAW, XDIM,
YDIM, GCB)
```

All arguments have the same meaning as in subroutine WINDOW.

For any element of ARRAY equal to zero, no action is taken.

For any non-zero elements the corresponding bit in the grid is turned on.

Note

Since no action is taken for ARRAY entries of zero, the original bit value is retained for that entry in the grid.

Subroutine INIGRD

Purpose

The purpose of the subroutine INIGRD is to initialize the disk constants table and to define one or more grids.

Usage

```
INTEGER*2 TAPE(66), GCB1(271), SIZE1, GCB2(79), SIZE2
SIZE1=4
SIZE2=1
CALL INIGRD (TAPE,GCB1,SIZE1,GCB2,SIZE2,...GCB4,SIZE4)
```

Only the first three arguments are required, allowing the definition of one to four grids.

TAPE is an array 132 bytes, long used for magnetic tape.
GCB1 is an array (128*SIZE1) + 30 bytes long.
SIZE1 specifies the length of the buffer in lines.

Note

This program must be called before any other grid system subroutines.

The first 6 elements of a grid control block (GCB) specify information about the corresponding grid. If the user calls INIGRD, these values are filled in automatically, and the first GCB specified is established as the default for other fortran-callable subroutines. Alternatively, the user may fill in these values himself as follows:

```
BIAS     DC x'2000'      Disk address of start of grid
BADTRK   DC x'FFFF'      Can be used to specify bad track
                         on disk
NLIB     DC 4            Number of lines in buffer (SIZE)
BOTLIN   DC 0            Number of first line in grid
TOPLIN   DC 1023         Number of top line in grid
LEFT     DC 0
RIGHT    DC 1023
BFST     DC A(BUFFER)    Address of buffer
         DS 14           Used by the system
BUFFER   DS SIZE*128
```

Subroutine WINDOW

Purpose
The purpose of the subroutine WINDOW is to transfer a portion of the grid to a FORTRAN array.

Usage
INTERGER*2 ARRAY (XDIM,YDIM), SCALE, XBIAS, YBIAS, IERR, DRAW, XDIM, YDIM

CALL WINDOW(ARRAY, SCALE, XBIAS, YBIAS, IERR, DRAW, XDIM, YDIM)

The grid consists of 1024 by 1024 squares numbered as shown:

Thus one square of the grid corresponds to four units on the Sylvania tablet.

SCALE — specifies how many grid squares correspond to one element of the array. The value of each element of the array is the number of grid squares "turned on" within the corresponding spot on the grid.

XBIAS, YBIAS — specify the location of the lower left hand corner of the window.

IERR
= 0 if all is well
= 1 if the specified parameters would force the window off the tablet. The values of XBIAS and YBIAS will be modified in the FORTRAN program to make the window fall within the range of the tablet.
= 2 if the SCALE*LARGEST_DIMENSION 1024 (the size of the tablet). The valve will be adjusted.

DRAW — is an optional variable.
1 = A square will be drawn on the ARDS corresponding to the portion of the original drawing included in the window.
0 = No square will be drawn (the default).

XDIM — is an optional variable which specifies the dimension in the X direction. Default is 32.

YDIM — is an optional variable which specifies the dimension in the X direction. Default is to the value of XDIM.

GCB — is an optional variable which specifies the grid to be used (see INIGRD).

Subroutine WWWDOW

Purpose
The purpose of subroutine WWWDOW is to write out an array on the grid.

Usage
INTEGER*2(ARRAY, SCALE, XBIAS, YBIAS, IERR, DRAW, XDIM, YDIM)

Appendix III

COMPUTER LISTINGS FOR STRAIN

```
0000R                   EXTRN DSKTAP,SKIP,BSTORE
0000R                   EXTRN DISKST,INITAP
0000R                   EXTRN PTMAX,JNAME
0000R                   EXTRN ENDN,GETLAT
0000R                   EXTRN MARK,IODEV
0000R                   EXTRN OFFSET,TAPERR,CONSTR,PTMAX
0000R                   ENTRY PTCALC,PERROR,PRLOOP

0000            STORE   EQU   0
0002            STORE2  EQU   2

0006            INCREM  EQU   6


                *  CALL PTCALC(STATUS,SCRATCH.ARR,SC.LENGTH,[N
                *                STATUS=>0 OK
                *                      =>-1 STORAGE NOT ALLOCA
                *                       => 1 RAN OUT OF SPACE
                *                SCRATCH.ARR=>33*6 BYTE ARRAY
                *                SC.LENGTH=>SIZE OF ARRAY IN H


                *
                *          IF NO NUMBER, INITIALIZE & STRAIT
                *          IF NUMBER NEGATIVE, ONTINUE
                *          IF NUMBER NON-NEGATIVE,STRAIGHTEN
                *               (0=1)


0000R 4300              B     PTCALC
      0024R
0004R           SAVER   DS    32
0022R           SAV15   EQU   *-2
0024R D000      PTCALC  STM   0,SAVER
      0004R
0028R 48AF              LH    R0,0(15)
      0000
002CR C5A0              CLHI  R0,4
      0004
0030R 4280              BL    DONE
      0130R
0034R C5A0              CLHI  R0,8
      0008
0038R 4380              BNL   OK
      0044R
003CR C8A0              LHI   R0,-1
      FFFF
0040R 4300              B     PERROR
      0124R
0044R E110      OK      SVC   1,REW
      0160R
0048R 48AF              LH    R0,4(15)
```

```
                0004
004CR 26A6              AIS     10,INCREM
004ER 40A0              STH     10,OFFSET
                0000F
0052R 48D0              LH      13,DSKTAP
                0000F
0056R 4330              BZ      NOEN
                006ER
005AR 48DF              LH      13,6(15)
                0006
005ER 4AAD              AH      10,0(13)
                0000
0062R 4AAD              AH      10,0(13)
                0000
0066R CBA0              SHI     10,INCREM+INCREM
                000C
006AR 40A0              STH     10,ENDN
                0000F
006ER 41B0      NOEN    BAL     15,CONSTA
                0000F
0072R 0004              DC      4
0074R 015ER             DC      SIZE
0076R 40B0              STH     14,PTMAX
                0000F
007AR 48A0              LH      10,MARK         ********MARKED
                0000F
007ER 40A0              STH     10,DISKST
                0000F
                *READ IN THE FIRST BLOCK OF DATA
0082R 4850              LH      5,DSKTAP
                0054R
0086R 4210              BM      TAPEI
                0092R
008AR 4220              BP      PASS
                00DCR
008ER 4300              B       NODAT
                00EER
0092R C8A0      TAPEI   LHI     10,-1
                FFFF
0096R 40A0              STH     10,DISKST
                0080R
009AR 48F0              LH      15,SAVER+32
                0022R
009ER 48AF              LH      10,0(15)
                0000
00A2R C5A0              CLHI    10,10
                000A
00A6R 4380              BNL     COUNT
                00B0R
00AAR 07AA              XHR     10,10
00ACR 4300              B       INIT
                00C4R
```

```
00B0R 48DF     COUNT    LH     13,8(15)
      0008
00B4R 48AD              LH     10,0(13)
      0000
00B8R 4210              BM     PASS
      00DCR
00BCR C8BA              LHI    11,1(10)
      0001
00C0R 40BD              STH    11,0(13)
      0000
00C4R 41F0     INIT     BAL    15,INITAP
      0000F
00C8R C5A0     CHECK    CLHI   10,2
      0002
00CCR 4280              BL     PASS
      00DCR
00D0R 41F0              BAL    15,SKIP
      0000F
00D4R CBA0              SHI    10,1
      0001
00D8R 4300              B      CHECK
      00C8R
00DCR 48D0     PASS     LH     13,OFFSET
      0050R
00E0R 48E0              LH     14,ENDN
      006CR
00E4R 26E5              AIS    14,INCREM-1
00E6R 41B0              BAL    15,GETDAT
      0000F
00EAR 4200              NOP    NONE
      0130R
                *SET R9 FOR FIRST LINE END
00EER 4890     NODAT    LH     9,OFFSET
      00DER
00F2R C8A0              LHI    10,X'F000'
      F000
00F6R 45A9              CLH    10,STORE(9)
      0000
00FAR 4330              BE     GO
      0D06R
00FER 48A0              LH     10,DSKIAP
      0084R
0102R 4210              BM     PASS
      00DCR
0106R 2796     GO       SIS    9,INCREM
0108R 40A9              STH    10,STORE(9)
      0000
010CR C8B0              LHI    14,GOTIT
      0114R
0110R E180              SVC    8,UNAME
      0000F
0114R 07AA     GOTIT    XHR    10,D(
```

```
  0116R 40A9              STH    10,STORE2(9)
        0002
  011AR 40A0              STH    10,ESTORE
        000F
                *GO STRAIGHTEN
  011ER 4100              BAL    0,TANDRV
        000F
  0122R 07AA              XHR    10,10
  0124R 48B0    PERROR    LH     15,SAV15
        0022R
  0128R 48BF              LH     11,2(15)
        0002
  012CR 40AB              STH    10,0(11)
        0000
  0130R 48D0    DONE      LH     15,LSKTAP
        0100R
  0134R 4310              BNM    EXIT
        013CR
  0138R 41D0              BAL    15,SKIP
        00D2R
  013CR C8D0    EXIT      LHI    15,X'0D'
        000D
  0140R 48D0              LH     14,IODEV
        000F
  0144R 9DED              SSR    14,13
  0146R 4290              BTC    9,*-2
        0144R
  014AR 9AEF              WDR    14,15
  014CR DD00              LM     0,SAVER
        0004R
  0150R 4AFF              AH     15,0(15)
        0000
  0154R 030F              BR     15

  0156R C8A0    PRLOOP    LHI    10,1
        0001
  015AR 4300              B      PERROR
        0124R
  015ER 000C    SIZE      DC     12
  0160R C002    REW       DC     X'C002',0
        0000
  0164R                   END
NO ERRORS

* BSTORE  011CR
  CHECK   00C8R
* CONSTR  0070R
  COUNT   00B0R
* DISKST  0098R
  DONE    0130R
* DSKTAP  0132R
* ENDN    00E2R
  EXIT    013CR
```

```
* GETDAT   00E8R
  GO       0106R
  GOTIT    0114R
  INCREM   0006
  INIT     00C4R
* INITAP   00C6R
* IODEV    0142R
* MARK     007CR
  NODAT    00EER
  NOEN     006ER
* OFFSET   00F0R
  OK       0044R
  PASS     00DCR
* PERROR   0124R
* PRLOOP   0156R
* PTCALC   0024R
* PTMAX    0078R
  REW      0160R
  SAV15    0022R
  SAVER    0004R
  SIZE     015ER
* SKIP     013AR
  STORE    0000
  STORE2   0002
* TANDRV   0120R
  TAPEI    0092R
* UNAME    0112R
```

****

****

```
                *TANDRV,CSTART,ENDSEG,CFIX,AND INTERS USE 'CO
                *  TO STORE POINTERS TO THE BEGINNING AND END
                *  SEGMENTS.  WHEN FILLED, THE ARRAY 'CORNER'
                *     CORNER(0) POINTER TO 1ST POINT ON 1ST L
                *     CORNER(2) PTR TO LAST PT ON SEGMENT BEF
                *     CORNER(4) SLOPE OF THE 1ST SEGMENT( DY/
                *          (WHICH MOVES DECIMAL PLACE 6 BITS
                *     CORNER(6) POINTER TO 1ST POINT AFTER TH
                *          1ST POINT OF 2ND SEGMENT
                *     CORNER(8) POINTER TO LAST POINT ON 2ND
                *     CORNER(A) SLOPE OF 2ND SEGMENT
                *     CORNER(C) POINTER TO START OF 3RD SEGME
                * THIS SERIES CAN EITHER BE CUT OFF AT CORNER
                * IF THE PEN IS LIFTED


0000R                    EXTRN SAVEC,EOB,PUSHER,GETSQ
0000R                    EXTRN CSTART,ENDSEG
0000R                    EXTRN RATER,EXTRMR,SEX,SEY
0000R                    EXTRN DISKST,GETDAT
0000R                    EXTRN INTERV,RTEST0,RMAX2,PMAX2
0000R                    EXTRN TANGNT,TRNTST,TANDIF
0000R                    ENTRY TANDRV,RETERN,CNEXT,NOEND
0000R                    ENTRY TANDRI
0000R                    EXTRN DATP,CORNCT,EDIN
0000R                    EXTRN OFFSET,DSKTAP

0000               STORE  EQU  0
0002               STORE2 EQU  2


0008               PTSIZE EQU  8
0006               INCREM EQU  6


0000R 4000         TANDRV STH  0,RETERN
      0130R
0004R 0B55                SHR  5,5              SET UP POINTER
0006R 4050                STH  5,CORNCT         FOR 'CORNER' LI
      0000F
000AR 4050                STH  5,DATP
      0000F
000ER 4D00                BAL  D,GETSQ
      0000F
0012R 0B77         TANDRI SHR  7,7              ENTRY FOR BEGIN
0014R 4070                STH  7,RMAX2          INIT FASTEST DW
      0000F
0018R 4070                STH  7,PMAX2          INIT HARDEST PR
```

```
                0000F
001CR 4820              LH      2,CORNCT        GET 'CORNER' PO
                000BR
0020R 4819      CNEXT   LH      1,STORE(9)      AM I AT AN ENDP
                000D
0024R C910              CHI     1,X'8000'
                F00D
0028R 4220              BP      FLAGED
                0030R
002CR 0777              XHR     7,7
002ER 4070              STH     7,SQFLAG
                0088R
0032R 0889              LHR     8,9
0034R 4B80              SH      8,OFFSET
                000DF
0038R 48D0              LH      13,DISKST
                000DF
003CR CDD0              SLHL    13,7
                0007
0040R 0A8D              AHR     8,13            SET UP BACK POI
0042R C410              NHI     1,X'C000'       TO BLOCK ON DIS
                0000
0046R 0618              OHR     1,8             INDICATE ENDPOI
0048R 4012              STH     1,DATP(2)       AND SAVE
                000CR
004CR 2696      PBUMP   AIS     9,INCREM
004ER 4590              CLH     9,ENDN
                0000F
0052R 4280              BL      LOW
                007AR
0056R 4330              BE      LOW
                007AR
005AR 48D0              LH      13,DSKTAP
                0000F
005ER 4330              BZ      ENDFL
                015ER
0062R 48D0              LH      13,OFFSET
                0036R
0066R 48E0              LH      14,ENDN
                0050R
006AR CAE0              AHI     14,INCREM-1
                0005
006ER 41F0              BAL     15,GETDAT
                0000F
0072R 4200              NOP     ENDFL
                015ER
0076R 4890              LH      9,OFFSET
                0064R
007AR 2671      LOW     AIS     7,1             INDICATE A STAR
007CR 4300              B       CNEXT           LOOP AGAIN
                0020R
0080R 0877      FLAGED  LHR     7,7             WHEN NOT AT END
```

```
0082R 4330            BZ     NEND            LOOK FOR START
      00D8R
0086R C870            LHI    7,0
      0000
0088R          SQFLAG EQU    *-2
008AR 4220            BP     PBUMP
      004CR
008ER C870            LHI    7,X'8000'
      8000
0092R 4570            CLH    7,SEX
      000OF
0096R 4330            BE     NOSQ
      00C0R
009AR 4879            LH     7,STORE(0)
      0000
009ER 4570            CLH    7,SEX
      0094R
00A2R 4230            BNE    NOSQ
      00C0R
00A6R 4879            LH     7,STORE2(9)
      0002
00AAR 4570            CLH    7,SEY
      000OF
00AER 4230            BNE    NOSQ
      00C0R
00B2R 4100            BAL    1,GETSQ
      0010R
00B6R 2471            LIS    7,1
00B8R 4070            STH    7,SQFLAG
      0088R
00BCR 4300            B      PBUMP
      004CR
00C0R 4D00    NOSQ    BAL    13,SAVEC
      000OF
00C4R C8A0    STEND   LHI    10,X'800'
      0800
00C8R 40A0            STH    10,RTESTC       FORCE IMMEDIATE
      000OF
00CCR 0B55            SBR    5,5
00CER 4100            BAL    1,NOEND         GET 1ST PT, CHE
      00F0R
00D2R 4100            BAL    1,TANGNT        GET ARCTAN FOR
      0000F
00D6R 2652            AIS    5,2
00D8R 4D00    NEND    BAL    13,NOEND        GET NEXT PT, CH
      00F0R
00DCR 4D00            BAL    13,TANGNT       GET NEXT ARCTAN
      00D4R
00E0R 4D00            BAL    13,TRATST       CHECK FOR CHANG
      000OF
00E4R 4510            CLH    1,TANDIF        S IT GREATER T
      000OF
```

```
00E8R 4220          BP    CSTART          YES: CORNER HAS
      0000F
00ECR 4300          B     NEND            ELSE RETURN FOR
      00D8R
                    *

                    *THIS ROUTINE CHECKS FOR END OF SEGMENT FLAG
                    *  DATA WITHIN AN INTERVAL OF CURRENT POINTER
                    * IF IT FINDS ONE, EXIT IS TO ENDSEG

00F0R 4000  NOEND   STH   0,EXIT
      015CR
00F4R 41F0          BAL   15,PUSHER       RETURNS WITH PR
      0000F
00F8R 41F0          BAL   15,RATER
      0000F
00FCR 0889          LHR   8,9
00FER 08A9          LHR   10,9
0100R 4AA0          AH    10,INTERV       GET POINTER TO
      0000F
0104R 4818  LOOP    LH    1,STORE(8)      LOOK TO SEE IF
      0000
0108R C910          CHI   1,X'F000'
      F000
010CR 4320          BNP   ENDSEG
      0000F
0110R 4980          CH    8,ENDN          AM I OUT OF DAT
      0068R
0114R 4320          BNP   ENUF            NO , GO ON
      013CR
0118R 08B9          LHR   11,9            YES,
011AR 41D0          BAL   15,ECB          SAVE OLD POINT
      0000F
011ER 48D0          LH    13,OFFSET
      0078R
0122R 48B0          LH    14,ENDN
      0112R
0126R CAE0          AHI   14,INCREM-1
      0005
012AR 41B0          BAL   15,GETDAT
      0070R
012ER 4200          NOP   0
      0000
0130R       RETERN  EQU   *-2
0132R C889          LHI   8,-INCREM(9)
      FFFA
0136R 0898          LHR   9,8             RESET REGISTERS
0138R C8A8          LHI   10,INTERV(8)
      0102R
013CR 0598  ENUF    CLHR  9,8
```

```
 013ER 4330          BE     NEXT1
       0148R
 0142R 0818          LHR    13,8
 0144R 41E0          BAL    15,EXTRMR        LOOK FOR SMALL
       000OF
 0148R CA80    NEXT1 AHI    8,INCREM         GO FOR NEW POIN
       0006
 014CR 05A8          CLHR   10,8             IF PAST END
 014ER 4380          BNL    LOOP             OF NEXT INTERVA
       0104R
 0152R 4819          LH     1,STORE(9)       YOU'RE OK
       0000
 0156R 4839          LH     3,STORE2(9)
       0002
 015AR 4300          B      *
       015AR
 015CR         EXIT  EQU    *-2



 015ER 4810    ENDFL LH     0,RETERN
       0130R
 0162R 0300          BR     0
 0164R               END
```

NO ERRORS

```
* CNEXT   0020R
* CORNCT  001ER
* CSTART  00EAR
* DATP    004AR
* DISKST  003AR
* DSKTAP  005CR
  ENDFL   015ER
* ENDN    0124R
* ENDSEG  010ER
  ENUF    013CR
* EOB     011CR
  EXIT    015CR
* EXTRMR  0146R
  FLAGED  0080R
* GETDAT  012CR
* GETSQ   00B4R
  INCREM  0006
* INTERV  013AR
  LOOP    0104R
  LOW     007AR
  NEND    00D8R
  NEXT1   0148R
* NOEND   00F0R
  NOSQ    00C0R
* OFFSET  0120R
  PBUMP   004CR
```

```
* PMAX2    001AR
  PTSIZE   0008
* PUSHER   00F6R
* RATER    00FAR
* RETERN   0130R
* RMAX2    0016R
* RTESTC   00CAR
* SAVEC    00C2R
* SEX      00A0R
* SEY      00ACR
  SQFLAG   0088R
  STENL    00C4R
  STORE    0000
  STORE2   0002
* TANDIF   00E6R
* TANDRI   0012R
* TANDRV   0000R
* TANGNT   00DER
* TRNTST   00E2R

*****************************************************************
```

```
0000R                       ENTRY GETSQ,SEX,SEY

0007            WRK2        EQU   7

0000R 0777      GETSQ       XHR   WRK2,WRK2
0002R 4070                  STH   WRK2,DATA
      0068R
0006R E110                  SVC   1,RTSQ
      0060R
000AR 4870                  IH    WRK2,STAT
      0062R
000ER 4310                  BNM   NOENI
      001ER
0012R C870      NOIATA      IHI   WRK2,X'8000'
      8000
0016R 4070                  STH   WRK2,SEX
      006AR
001AR 4300                  B     EXIT
      005ER
001ER 4870      NOEND       IH    WRK2,DATA
      0068R
0022R 4330                  BZ    NOIATA
      0012R
0026R 2772                  SIS   WRK2,2
0028R 4330                  BZ    SQF
      0042R
002CR E110                  SVC   1,RDSQ
      0060R
0030R 4870                  LH     RK2,DATA
      0068R
0034R 2771      RDLOOP      SIS   WRK2,1
0036R 4210                  BM    GETSQ
      0000R
003AR E110                  SVC   1,RTSQ
      0060R
003ER 4300                  B     RDLOOP
      0034R
0042R E110      SQF         SVC   1,RTSQ
      0060R
0046R E110                  SVC   1,RDSQ
      0060R
004AR 4870                  IH    WRK2,DATA
      0068R
004ER 4070                  STH   WRK2,SEX
      006AR
0052R E110                  SVC   1,RTSQ
      0060R
0056R 4870                  IH    WRK2,DATA
      0068R
005AR 4070                  STH   WRK2,SEY
      006CR
005ER 0300      EXIT        BR    0
```

```
 0060R 4002     RDSQ     DC     X'4002'
 0062R 0000     STAT     DC     0
 0064R 0068R              DC     DATA
 0066R 0069R              DC     DATA+1
 0068R 0000     DATA     DC     0
 006AR 0000     SEX      DC     0
 006CR 0000     SEY      DC     0
 006ER                   END

NO ERRORS

  DATA     0068R
  EXIT     005ER
* GETSQ    0000R
  NODATA   0012R
  NOEND    001ER
  RDLOOP   0034R
  RDSQ     0060R
* SEX      006AR
* SEY      006CR
  SQF      0042R
  STAT     0062R
  WRK2     0007
```

****

```
0000R                   ENTRY PUSHER,PMAX1,PMAX2,RPFIG
0000R                   EXTRN INTERV

0004            STORE4  EQU   4
0006            INCREM  EQU   6

0000R D0D0      PUSHER  STM   14,SAV2
      002ER
0004R 08E9              LHR   14,9
0006R 08F9              LHR   15,9
0008R 4AB0              AH    15,INTERV
      0000F
000CR 48 E      LOOP    LH    0,STORE4(14)
      0004
0010R CC 0              SRHL  0,2
      0002
0014R 45 0              CLH   0,PMAX2
      004CR
0018R 4280              BL    HOP1
      0020R
001CR 4000              STH   0,PMAX2
      004CR
0020R 26E6      HOP1    AIS   14,INCREM
0022R 05FE              CLHR  15,14
0024R 438C              BNL   LOOP
      000CR
0028R D1D0              LM    14,SAV2
      002ER
002CR 030F              BR    15

002ER           SAV2    DS    4

0032R D0D0      RPFIG   STM   14,SAV2
      002ER
0036R C8B0              LHI   15,16
      0010
0038R           SIXTEN  EQU   *-2
003AR 0BF0              SHR   15,0
003CR 0CEB              MHR   14,11
003ER 4DE0              DH    14,SIXTEN
      0038R
0042R 08BF              LHR   11,15
0044R D1E0              LM    14,SAV2
      002ER
0048R 030F              BR    15

004AR 0000      PMAX1   DC    0
004CR 0000      PMAX2   DC    0
004ER                   END

NO ERRORS

  HOP1    0020R
```

```
  INCREM  0006
* INTERV  000AR
  LOOP    000CR
* PMAX1   004AR
* PMAX2   004CR
* PUSHER  00000R
* RPFIG   0032R
  SAV2    002ER
  SIXTEN  0038R
  STORE4  00004

**********************************************************************
```

```
0000R                    ENTRY CSTART,LINE,TANFAC,SLOPER,SLOPE
0000R                    ENTRY SAVEC,THOLD
0000R                    EXTRN DATP
0000R                    EXTRN NOENI,TRNTST,TANDIF,TANGNT
0000R                    EXTRN TANDRI,TAN,FCORN
0000R                    EXTRN CORNCT,CORNER,INTERV
0000R                    EXTRN DISKST,RTESTC
0000R                    EXTRN INTERH,RMAX1,RMAX2
0000R                    EXTRN OFFSET

0000            STORE    EQU   0
0002            STORE2   EQU   2

                *REGISTERS:  0--BAL
                *            1--WORKING
                *            2--CORNCT
                *            3--
                *            4--
                *            9--STORE POINTER
                *            11-

0006            INCREM   EQU   6

0000R 2796      CSTART   SIS   9,INCREM
0002R 2752               SIS   5,2
0004R 4820               LH    2,CORNCT
      0000F
0008R 2622               AIS   2,2
000AR 4100               BAL   0,SAVEC
      007ER
000ER 4810               LH    1,DISKST
      0000F
0012R CD10               SLHL  1,7
      0007
0016R 0809               LHR   0,9
0018R 4B00               SH    0,OFFSET
      0000F
001CR 0A00               AHR   1,0
001ER 4012               STH   1,DATP(2)
      0000F
0022R 4020               STH    ,CORNCT
      0006R
0026R 4100               BAL   1,LINE
      00ACR
002AR 4100      NCEND1   BAL   0,NOEND
      0000F
002ER 4100               BAL   0,TANGNT
      0000F
0032R 4100               BAL   0,TRNTST
      0000F
0036R 0811               LHR   1,1
0038R 4330               BZ    NCEND1
```

```
      002AR
003CR 4510          CLH   1,TANDIF
      0000F
0040R 4380          BNL   NCEND1
      002AR
0044R 2796          SIS   9,INCREM
0046R 4820          LH    2,CORNCT
      0024R
004AR 2622          AIS   2,2
004CR 4100          BAL   0,SAVEC
      007ER
0050R 4800          LH    0,DISKST
      0010R
0054R CD00          SLHL  0,7
      0007
0058R 08B9          LHR   11,9
005AR 4BB0          SH    11,OFFSET
      001AR
005ER 0AB0          AHR   0,11
0060R 4002          STH   0,DATP(2)
      0020R
0064R 4020          STH   0,CORNCT
      0048R
0068R 2622          AIS   2,2
006AR C520          CLHI  2,8
      0008
006CR               VIII  EQU   *-2
006ER 4230          BNE   FCORN
      0000F
0072R 48B0          LH    11,RMAX2
      0000F
0076R 40B0          STH   11,RMAX1
      0000F
007AR 4300          B     TANDRI
      0000F
                    **
                    *

007ER 4010    SAVEC STH   1,SAV1
      00A4R
0082R 40A0          STH   10,SAVA
      00A8R
0086R C8A0          LHI   10,THOLI
      013CR
008AR 0AA2          AHR   10,2
008CR 0AA2          AHR   10,2
008ER 4819          LH    1,STORE(9)
      0000
0092R 401A          STH   1,STORE(10)
      0000
0096R 4819          LH    1,STORE2(9)
      0002
```

```
009AR 401A              STH   1,STORE2(10)
      0002
009ER 40A2              STH   10,CORNER(2)
      000F
00A2R C810              LHI   1,0
      0000
00A4R             SAV1  EQU   *-2
00A6R C8A0              LHI   10,0
      0000
00A8R             SAVA  EQU   *-2
00AAR 0300              BR    0
                  *
00ACR             LINE  EQU   *
00ACR CB50        OUT   SHI   5,2
      0002
00B0R 4815              LH    1,TAN(5)
      000F
00B4R 0855              LHR   5,5
00B6R 4320              BNP   OKT
      00C2R
00BAR C510              CLHI  1,X'64AE'
      64AE
00BCR             TWOPI EQU   *-2
00BER 4330              BE    OUT
      00ACR
00C2R 40D0        OKT   STH   1,TAN
      00B2R
00C6R 4820              LH    2,CORNCT
      0066R
00CAR 41D0              BAL   15,SLOPER
      00D6R
00CER 4020              STH   2,CORNCT
      00C8R
00D2R 2452              LIS   5,2
00D4R 0300              BR    0
                  *
                  *
00D6R 40F0        SLOPER STH  15,H15
      00F4R
00DAR 4812              LH    1,CORNER(2)
      00A0R
00DER 4831              LH    3,STORE(1)
      0000
00E2R 4851              LH    5,STORE2(1)
      0002
00E6R 2722              SIS   2,2
00E8R 41F0              BAL   15,SLOPE1
      00F6R
00ECR 2624              AIS   2,4
00EER 4052              STH   5,CORNER(2)
      00DCR
00F2R 4300              B     *
```

```
        00F2R
00F4R                   H15     EQU     *-2
                        *


                        *
00F6R 4812      SLOPE1  LH      1,CORNER(2)
        00F0R
00FAR 4B51              SH      5,STORE2(1)
        0002
00FER 4B31              SH      3,STORE(1)
        0000
0102R 4230              BNZ     FINITE
        010CR
0106R 2431              LIS     3,1
0108R 4C40              MH      4,VIII
        006CR
010CR 4C40      FINITE  MH      4,TANFAC
        013AR
0110R 0874      LOOP1   LHR     7,4
0112R 0885              LHR     8,5
0114R 0D43              DHR     4,3
0116R 0585              CLHR    8,5
0118R 4230              BNE     OK
        0138R
011CR 0574              CLHR    7,4
011ER 4230              BNE     OK
        0138R
0122R 0844              LHR     4,4
0124R 4330              BZ      OK
        0138R
0128R 4210              BP      MINUS
        0134R
012CR C850              CHI     5,X'7FFF'
        7FFF
0130R 4300              B       OK
        0138R
0134R C850      MINUS   CHI     5,X'8000'
        8000
0138R 030F      OK      BR      15
                        *
013AR 0040      TANFAC  DC      X'40'
013CR           THOLD   IS      32
015CR                   END

NO ERRORS

* CORNCT  00D0R
* CORNER  00F8R
* CSTART  0000R
* DATP    0062R
* DISKST  0052R
* FCORN   0070R
```

```
  FINITE  010CR
  H15     00F4R
  INCREM  0006
**INTERH  0000
**INTERV  0000
* LINE    00ACR
  LOOP1   0110R
  MINUS   0134R
  NCEND1  002AR
* NOENT   002CR
* OFFSET  005CR
  OK      0138R
  OKT     00C2R
  OUT     00ACR
* RMAX1   0078R
* RMAX2   0074R
**RTESTC  0000
  SAV1    00A4R
  SAVA    00A8R
* SAVEC   007ER
* SLOPE1  00F6R
* SLOPER  00D6R
  STORE   0000
  STORE2  0002
* TAN     00C4R
* TANDIF  003ER
* TANDRI  007CR
* TANFAC  013AR
* TANGNT  0030R
* THOLD   013CR
* TRNTST  0034R
  TWOPI   00BCR
  VIII    006CR

*****************************************************************
```

```
0000R                   EXTRN STABS,ATANUR
0000R                   ENTRY TAN,DIST,INTERH
0000R                   ENTRY TANGNT,TRNTST,IN ERV-,TANDIF

0006            INCREM  EQU   6

0000            STORE   EQU   0
0002            STORE2  EQU   2

                *
                *
                * TANGNT:  READS POINTS FROM STORE, FINDS DEL
                *       SEGMENTS, FINDS ARCTANGNT OF ANGLE
                *       AND STORES IT IN A LIST OF ARCTANGENTS
                *      R1 HAS STORE(9)
                *      R3 HAS STORE2(9)
                *      R9 HAS INDEX FROM POINTS
                *      R5 HAS TAN INDEX
                *      R4 WORKING
                *      R15 BAL ATANUR,STABS
                *      R0 RETURN ADDRESS
                *
                *
0000R 4A90      TANGNT  AH    9,INTERV
      0006R
0004R 4B39              SH    3,STORE2(9)       DELTA Y
      0002
0008R 4B19              SH    1,STORE(9)        DELTA X
      0000
000CR 4230              BNZ   FINITE
      0028R
0010R 2411              LIS   1,1
0012R 0833              LHR   3,3
0014R 4230              BNZ   ENLARG
      0024R
0018R C810      NIL     LHI   1,X'64AE'
      64AE
001AR           TWOPI   EQU   *-2
001CR 4015              STH   1,TAN(5)
      00C2R
0020R 4300              B     EXIT
      0054R
0024R CF30      ENLARG  SLHA  3,4
      0004
0028R 41F0      FINITE  BAL   15,DIST
      00A8R
002CR 4010              STH   1,DELTAX
      011AR
0030R 4030              STH   3,DELTAY
      010CR
0034R 41F0              BAL   15,ATANUR
      0000F
```

```
0038R 010CR             DC     A(DELTAY)
003AR 0D0AR             DC     A(DELTAX)
003CR 010ER             DC     A(ANGLE)
003ER 4810              LH     1,ANGLE
      010ER
0042R 4830              LH     3,ANGLE+2
      0110R
0046R CF10              SLHA   1,12
      000C
004AR CE30              SRHA   3,3
      0003
004ER 0A13              AHR    1,3
0050R 4015              STH    1,TAN(5)
      00C2R
0054R C450    ENDT      NHI    5,X'3F'
      003F
0058R 4015              STH    1,TAN(5)
      00C2R
005CR 4B90              SH     9,INTERV
      0D06R
0060R 2696              AIS    9,INCREM
0062R 0300              BR     0
                *TRNTST:  LOOKS AT A LIST OF ARCTANGENTS TO S
                *         A TURN OCCURS SOMEWHERE WITHIN THEM
                *.
                *
                *USES REGS 0(RETURN),1,2,5(WHICH HAS VALUE OF
                *                TAN CHECKED),15(BAL)
                *.
0064R 0845    TRNTST    LHR    4,5
0066R 4815              LH     1,TAN(5)
      00C2R
006AR 4910              CH     1,TWOPI
      001AR
006ER 4380              BNL    ZERO
      00A2R
0072R 2742    PILOOP    SIS    4,2
0074R 42D0              BM     ZERO
      00A2R
0078R 4814              LH     1,TAN(4)
      00C2R
007CR 45D0              CLH    1,TWOPI
      001AR
0080R 433D              BE     PILOOP
      0072R
0084R 4B15              SH     1,TAN(5)
      00C2R
0088R 41F0              BAL    15,STABS
      000F
008CR 0821              LHR    2,1
008ER 4B10              SH     1,TWOPI
      001AR
```

```
 0092R 41F0              BAL    15,STABS
       008AR
 0096R 0521              CLHR   2,1
 0098R 4380              BNL    END
       009ER
 009CR 0812              LHR    1,2
 009ER 2652    END       AIS    5,2
 00A0R 0300              BR     0

 00A2R 0B11    ZERO      SHR    1,1
 00A4R 4300              B      END
       009ER
               *

               *
 00A8R 0873    DIST      LHR    7,3
 00AAR 08D1              LHR    13,1
 00ACR 0CCD              MHR    12,13
 00AER 0C67              MHR    6,7
 00B0R 0AD7              AER    13,7
 00B2R 0EC6              ACHR   12,6
 00B4R 08CC              LHR    12,12
 00B6R 023F              BNZR   15
 00B8R C5D0    DISTFL    CLHI   13,X'10'
       0010
 00BCR 4280              BL     NIL
       0018R
 00C0R 030F              BR     15
               *
               *
 00C2R         TAN       DS     66
 0104R         TANDIF    DS     2
 0106R         INTERV    DS     2
 0108R         INTERH    DS     2
 010AR         DELTAX    DS     2
 010CR         DELTAY    DS     2
 010ER         ANGLE     DS     2
 0110R         ANGLE2    DS     2
 0112R                   END

NO ERRORS

  ANGLE    010ER
  ANGLE2   0110R
* ATANUR    0036R
  DELTAX   010AR
  DELTAY   010CR
* DIST     00A8R
  DISTFL   00B8R
  END      009ER
```

```
   ENDT     0054R
   ENLARG   0024R
   FINITE   0028R
   INCREM   0006
*  INTERH   0108R
*  INTERV   0106R
   NIL      0018R
   PILOOP   0072R
*  STABS    0094R
   STORE    0000
   STORE2   0002
*  TAN      00C2R
*  TANDIF   0104R
*  TANGNT   0000R
*  TRNTST   0064R
   TWOPI    001AR
   ZERO     00A2R
```

****

```
                *RATER READJUSTS RATES EVERY 12 POINTS
                *THIS VERSION USES A GENERAL FUNCTION
                *  INTERH = INTERV = INTERVAL BETWEEN SLOPE C
                *  DELTH1 = DELT11 = DX FOR END TO END MATCH
                *  DELTH2 = DELT22 = DY FOR END TO END MATCH
                *  DELTH3 = DELTA3 = Y DIF IN CHEKR (CFIX)
                *  DELTH4 = DELTA4 = DX FOR INTERSECTIONS
                *  DELTH5 = DELTA5 = DY FOR INTERSECTIONS
                *  TANDIH = TANDIF = ANGLE CHANGE PERMISSIBLE
                *
                *
                *  DELTA1-3:  1/32 IN. TO 3/8 IN.
                *               12 COUNTS + 8(RATE)
                *  DELTA4-5:  1/16 IN. TO 3/8+ IN.
                *               23 COUNTS + 8(RATE)
                *  INTERV = 4 * (18 - R)/2 (SKIP 4 TO 8 POINT
                *  TANDIF = PI/90 + (PI/9 * R) (4 TO 34 DEGR
                *
                *

0005            INCREM  EQU   5

0000R                   EXTRN INTERV,RFFIG
0000R                   EXTRN INTERH,TANDIF
0000R                   ENTRY TANDIH,RATER,RMAX1,RMAX2,RTESTC
0000R                   ENTRY T1,EIGHTH
0000R                   EXTRN FUNCT,OFFSET

0000            STORE   EQU   0
0002            STORE2  EQU   2

0000R 48D0      RATER   LH    D0,RTESTC       HAV ENOUGH POIN
      010AR
0004R 4AD0              AH    D0,INTERV       ELAPSED SINCE I
      0000F
0008R 40D0              STH   D0,RTESTC       REFIGURED THE P
      010AR
000CR 45D0              CLH   D0,RTEST        IF NO
      010CR
0010R 028F              BLR   15              RETURN
0012R 4000              STH   0,ST0           ELSE SET UP FOR
      00BER
0016R 4090              STH   9,ST9
      00C2R
001AR 40F0              STH   15,ST15
      00C6R
001ER C8A9              LHI   10,-INCREM-INCREM(9)
      FFF4
0022R 0766              XHR   6,6
0024R 4060              STH   6,LENGTH
      0110R
0028R C80C              LHI   12,X'800C'
```

```
                F000
002CR 2796      LOWER   SIS     9,INCREM        LOOK AHEAD
002ER 459?              CLH     ?,OFFSET
                0000F
0032R 428C              BL      UP1
                0046R
0036R 49C9              CH      12,STORE(9)
                0000
003AR 4310              BNM     UP1
                0046R
003ER 05A9              CLFR    D0,9
0040R 4280              BL      LOWER
                002CR
0044R 2102              BTFS    0,2
0046R 2696      UP1     AIS     9,INCREM
0048R 48B9      LOOP1   LH      11,STORE(9)     OTHERWISE
                0000
004CR 48D9              LH      13,STORE2(9)    STEP THRU GETLE
                0002
0050R 2696              AIS     9,INCREM        TO COME UP
0052R 41F0              BAL     15,GETL         WITH RATE
                00C8R
0056R C560              CLHI    6,4
                0004
005AR 428C              BL      LOOP1
                0048R
005ER 48D0      NOW     LH      13,LENGTH
                0110R
0062R C8B0              LHI     11,16
                0010
0066R 0CCB              MHR     12,11
0068R 4DC0              DH      12,EIGHTH
                00E8R
006CR 0ACC              AHR     12,12
006ER 450C              CLH     12,EIGHTH
                00E8R
0072R 2382              BFFS    8,2
0074R 26D1              AIS     13,1
0076R 08ED              LHR     13,13
0078R 2232              BFBS    3,2
007AR 0CA6              MHR     D0,6
007CR 0DAD              DHR     10,13
007ER 086B              LHR     6,11
0080R C8B0      LONG    LHI     11,16
                0010
0084R C560              CLHI    6,16
                0010
0088R 4320              BNP     RATEUP
                0090R
008CR C860              LHI     6,16
                0010
0090R 0BB6      RATEUP  SHR     11,6            R11 HAS RATE
```

```
0092R 41F0 000F          BAL   15,RPFIG
0096R 45B0 0114R         CLH   11,RMAX2
009AR 4280 00A2R         BL    PARAMS
009ER 40B0 0114R         STH   11,RMAX2
00A2R 4100 00F4R PARAMS  BAL   0,T1
00A6R 40D0 0D0ER         STH   13,TANDIH
00AAR C8D0 000C  SAV12   LHI   13,INCREM+INCREM
00AER 40D0 0006R         STH   13,INTERV
00B2R 40D0 000FR         STH   13,INTERH
00B6R 0B99               SHR   9,9
00B8R 4090 010AR         STH   9,RTESTC
00BCR C800 0000          LHI   0,0
00BER          STC       EQU   *-2
00C0R C890 0000          LHI   9,0
00C2R          ST9       EQU   *-2
00C4R 4300 00C4R         B     *
00C6R          ST15      EQU   *-2

00C8R 2661     GETL      AIS   6,1
00CAR 48A9 0000          LH    10,STORE(9)
00CER C9A0 F000          CHI   10,X'B000'
00D2R 4320 005ER         BNP   NOW
00D6R 0BBA               SHR   11,10
00D8R 4BD9 0002          SH    13,STORE2(9)
00DCR 0CAB               MHR   10,11
00DER 0CCD               MHR   12,13
00E0R 0ABD               AHR   11,13
00E2R 4AB0 011CR         AH    11,LENGTH
00E6R C5B0 1300          CLHI  11,X'1300'       (X'45' COUNTS)*
00E8R          EIGHTH    EQU   *-2
```

```
00EAR 4380              BNL     LONG
      0080R
00EER 40B0              STH     11,LENGTH
      0110R
00F2R 03CF              BR      15


00F4R 41F0      T1      BAL     15,FUNCT
      000OF
00F8R 0000      AT1     DC      0
00FAR 0064              DC      100
00FCR 0000      BT1     DC      0
00FER 0064              DC      100
0100R 0300      CT1     DC      768
0102R 0064              DC      100
0104R 028A      DT1     DC      650
0106R 0000F             DC      A(TANDIF)
0108R 0300              BR      0




010AR           RTESTC  DS      2
010CR 0030      RTEST   DC      48
010ER           TANDIH  DS      2
0110R           LENGTH  DS      2
0112R           RMAX1   DS      2
0114R           RMAX2   DS      2
0116R                   END
```

NO ERRORS

```
  AT1       00F8R
  BT1       00FCR
  CT1       0100R
  DT1       0104R
* EIGHTH    00E8R
* FUNCT     00F6R
  GETL      00C8R
  INCREM    0006
* INTERH    00B4R
* INTERV    00B0R
  LENGTH    0110R
  LONG      0080R
  LOOP1     0048R
  LOWER     002CR
  NOW       005ER
* OFFSET    0030R
  PARAMS    00A2R
* RATER     0000R
  RATEUP    0090R
```

```
* RMAX1    0112R
* RMAX2    0114R
* RPFIG    0094R
  RTEST    010CR
* RTESTC   010AR
  SAV12    00AAR
  ST0      00BER
  ST15     00C6R
  ST9      00C2R
  STORE    0000
  STORE2   0002
* T1       00F4R
* TANDIF   0106R
* TANDIH   010ER
  UP1      0046R

*****************************************************************
```

```
0000R                   ENTRY FUNCT
                  *FUNCTION---R11 = RATE
                  *   F(RATE)=AA'(RATE)**3+B '(RATE)**2+CC'(RAT
                  *   WHERE A', B', & C' HAVE NEGATIVE EXPONENT
0000R 08DB        FUNCT   LHR   13,11
0002R 0CCB                MHR   12,11
0004R 0CCB                MHR   12,11
0006R 4CCF                MH    12,0(15)
      0000
000AR 4DCF                DH    12,2(15)
      0002
000ER 08AD                LHR   10,13
0010R 08DB                LHR   13,11
0012R 0CCB                MHR   12,11
0014R 4CCF                MH    12,4(15)
      0004
0018R 4DCF                DH    12,6(15)
      0006
001CR 0AAD                AHR   10,13
001ER 08EB                LHR   13,11
0020R 4CCF                MH    12,8(15)
      0008
0024R 4DCF                DH    12,10(15)
      000A
0028R 4ADF                AH    13,12(15)
      000C
002CR 0ADA                AHR   13,10
002ER 48CF                LH    12,14(15)
      000E
0032R 40DC                STH   13,0(12)
      0000
0036R 43CF                B     16(15)
      0010
003AR                     END

NO ERRORS

* FUNCT   0000R

*****************************************************************
```

```
0000R                   EXTRN PMAX1,PMAX2
0000R                   EXTRN RMAX1,RMAX2
0000R                   EXTRN CORNCT,INTERV,CORNER,LINE
0000R                   EXTRN CFIX,LINER
0000R                   EXTRN TANDRI,INTERH,DATP
0000R                   EXTRN DISKST,CHSA
0000R                   ENTRY GOTBAC,LINER2,CENDER
0000R                   ENTRY LINER2,HOLDEN
0000R                   ENTRY ENDSEG,FCORN
0000R                   EXTRN THOLD,BSTORE
0000R                   EXTRN OFFSET


0000            STORE   EQU   0
0002            STORE2  EQU   2
0004            STORE4  EQU   4
000C            STOREC  EQU   12

0006            INCREM  EQU   6

000DR 4820      ENDSEG  LH    2,CORNCT
      0000F
0010R 4080              STH   8,HOLD
      00BCR
0014R 2686              AIS   8,INCREM
0016R 4898              LH    9,STORE(8)
      0000
001AR C990              CHI   9,X'F000'         IF TWO FLAGS, G
      F000
001ER 4220              BP    SKIP
      0018R
0022R 0819              LHR   1,9               INTO REGISTER
0024R CB80      SKIP    SHI   8,INCREM+INCREM
      000C
0028R 0898              LHR   9,8               R9 POINTS 2 POI
002AR C410              NHI   1,X'C000'
      C000
002ER 4810              LH    0,DISKST
      0000F
0032R CD10              SLHL  0,7
      0007
0036R 0869              LHR   6,9
0038R 4B60              SH    6,OFFSET
      0000F
003CR 0616              OHR   1,6
003ER 0610              OHR   1,0
0040R C520              CLHI  2,10
      000A
0044R 4330              BE    GOT1
      005AR
0048R C520              CLHI  2,4
      0004
```

```
0040R 4330                BE      GOT1
      005AR
0044R 2622                AIS     2,2
0046R 4092                STH     9,CORNER(2)
      000OF
004AR 4012                STH     1,DATP(2)
      000OF
004ER 4020                STH      ,CORNCT
      0002R
0052R 4100                BAL     1,LINE
      000OF
0056R 4300                B       GOT2
      0062R
005AR 2722    GOT1        SIS     2,2
005CR 4012                STH     1,IATP(2)
      004CR
0060R 2622                AIS     2,2
0062R C520    GOT2        CLHI    2,4
      0004
0066R 4330                BE      LINER2
      00A2R
006AR 4100    GOTTEN      BAL     0,CFSA
      000OF
006ER 4100                BAL     1,CFIX
      000OF
0072R 00A2R               DC      LINER2
0074R 4860    GOTBAC      LH      6,PMAX1
      000OF
0078R CD60                SLHL    6,4
      0004
007CR 4660                OH      6,RMAX1
      000OF
0080R 0B22                SHR     2,2
0082R 4100                BAL     1,LINER
      000OF
0086R 2626                AIS     2,6
0088R 4860                LH      6,PMAX2
      000OF
008CR CD60                SLHL    6,4
      0004
0090R 4660                OH      6,RMAX2
      000OF
0094R 4D00                BAL     1,LINER
      0084R
0098R 0B22                SHR     2,2
009AR 4020                STH      ,CORNCT
      0050R
009ER 4300                B       ENDED
      00EAR
00A2R 4860    LINER2      LH      6,PMAX2
      008AR
00A6R CD60                SLHL    6,4
```

```
                0004
00AAR 4660              OH      6,RMAX2
                0032R
00AER 0B22              SHR     2,2
00B0R 4100              BAL     0,LINER
                0096R
00B4R 0B22              SHR     2,2
00B6R 4020              STH     2,CORNCT
                009CR
                *

00BAR C890      ENDED   LHI     9,0
                0000
00BCR           HOLDEN  EQU     *-2
00BCR           HOLD    EQU     *-2
00BER 4020              STH     2,DATP
                005ER
00C2R 0711              XHR     1,1
00C4R 4010              STH     1,ESTORE
                000F
00C8R 4810      ENDER   LH      1,INTERV
                000F
00CCR 4010              STH     1,INTERV
                000F
00D0R 4300              B       TANDAI
                000F
                *

                *
00D4R 4D00      FCORN   BAL     D,CFSA
                006CR
00D8R 4D00              BAL     D,CFIX
                0070R
00DCR 014CR             DC      CENDER
00DER 4860              LH      6,PMAX1
                0076R
00E2R CD60              SLHL    6,4
                0004
00E6R 4660              OH      6,RMAX1
                007ER
00EAR 4820              LH      2,RMAX2
                00ACR
00EER 4020              STH     2,RMAX1
                00E8R
00F2R 4820              LH      2,PMAX2
                00A4R
00F6R 4020              STH     2,PMAX1
                00E0R
00FAR 0B22              SHR     2,2
00FCR 4D00              BAL     D,LINER
```

```
                00B2R
  0100R 2626                    AIS     2,6
  0102R 0744                    XHR     4,4
  0104R 4832    SHLOOP          LH      3,DATP(2)
                00C0R
  0108R 4034                    STH      ,DATP(4)
                0106R
  010CR 2642                    AIS     4,2
  010ER 2622                    AIS     2,2
  0110R C520                    CLHI    2,14
                000E
  0114R 4280                    BL      SHLOOP
                0104R
  0118R 2742                    SIS     4,2
  011AR 4040                    STH     4,CORNCT
                00B8R
  011ER C830                    LHI     3,THOLD
                0000F
  0122R D0B0                    STM     14,SAV2
                0152R
  0126R 0722                    XHR     2,2
  0128R D1E3    STLOOP          LM      14,X'C'(3)
                000C
  012CR D0E3                    STM     14,0(3)
                0000
  0130R 2634                    AIS     3,4
  0132R 2621                    AIS     2,1
  0134R C520                    CLHI    2,4
                0004
  0138R 4280                    BL      STLOOP
                0128R
  013CR 2454                    LIS     5,4
  013ER 242A                    LIS     2,10
  0140R 4832                    LH      3,CORNER(2)
                0048R
  0144R 4035                    STH      ,CORNER(5)
                0142R
  0148R D1E0                    LM      14,SAV2
                0152R
  014CR 08B9    CENDER          LHR     11,9
  014ER 4300                    B       ENDER
                00C8R
                *
  0152R         SAV2            DS      F
  0156R                         END

NO ERRORS

* BSTORE   00C6R
* CENDER   014CR
* CFIX     00DAR
* CFSA     00D6R
* CORNCT   011CR
```

```
* CORNER  0146R
* DATP    010AR
* DISKST  0024R
  ENDED   00BAR
  ENDER   00C8R
* ENDSEG  00000R
* FCORN   00D4R
  GOT1    005AR
  GOT2    0062R
* GOTBAC  0074R
  GOTTEN  006AR
  HOLD    00BCR
* HOLDEN  00BCR
  INCREM  0006
* INTERH  00CAR
* INTERV  00CER
* LINE    0054R
* LINER   00FER
* LINER2  00A2R
* OFFSET  002ER
* PMAX1   00F8R
* PMAX2   00F4R
* RMAX1   00F0R
* RMAX2   00ECR
  SAV2    0152R
  SHLOOP  0104R
  SKIP    0018R
  STLOOP  0128R
  STORE   0000
  STORE2  0002
  STORE4  0004
  STOREC  000C
* TANDRI  00D2R
* THOLD   0120R
```

****

```
0000R                   ENTRY CFSA,MINIM
0000R                   EXTRN ATANUR,CORNER,DATP,BSTORE
0000R                   EXTRN STABS,INDEX,STOREX,STOREY
0000R                   EXTRN KIT,CFRTRN,PTMAX,GPOINT

0000          STORE     EQU   0
0002          STORE2    EQU   2

3258          PI        EQU   X'3258'
64AE          TWOPI     EQU   X'64AE'

0008          CORNR     EQU   8

0000R 4000    CFSA      STH   ,BACK+2
      015CR
0004R 2604              AIS   0,4
0006R 4000              STH   ,CFRTRN           IN CFIX
      0000F
000AR C880              LHI   CORNR,CORNER
      0000F
000ER 4828              LH    2,2(CORNR)
      0002
0012R 4832              LH    3,STORE(2)
      0000
0016R 4842              LH    4,STORE2(2)
      0002
001AR 4828              LH    2,0(CORNR)
      0000
001ER 48D0              LH    1,PTMAX
      0000F
0022R 4811              LH    1,6(1)
      0006
0026R 0512              CLHR  1,2
0028R 4280              BL    GOON1
      0058R
002CR 4020              STH   2,ANGLE
      0190R
0030R 41F0              BAL   15,GPOINT
      0000F
0034R 000A              DC    10
0036R 0020R             DC    PTMAX
0038R 0190R             DC    ANGLE
003AR 0188R             DC    ONE
003CR 018CR             DC    DELTAX
003ER 41D0              BAL   15,GPOINT
      0032R
0042R 000A              DC    10
0044R 0036R             DC    PTMAX
0046R 0190R             DC    ANGLE
0048R 018AR             DC    TWO
004AR 018ER             DC    DELTAY
004CR 4B30              SH    ,DELTAX
```

```
          018CR
0050R 4B40                SH     4,DELTAY
          018ER
0054R 4300                B      GOTAN
          0060R
0058R 4B32      GOON1     SH     3,STORE(2)
          0000
005CR 4B42                SH     4,STORE2(2)
          0002
0060R 4D00      GOTAN     BAL    13,ATNR
          0162R
0064R 0815                LHR    1,5
0066R 4828                LH     2,6(CORNR)
          0006
006AR 4832                LH     3,STORE(2)
          0000
006ER 4842                LH     4,STORE2(2)
          0002
0072R 4828                LH     2,8(CORNR)
          0008
0076R 4B32                SH     3,STORE(2)
          0000
007AR 4B42                SH     4,STORE2(2)
          0002
007ER 4100                BAL    1,ATNR
          0162R
0082R 0B15                SHR    1,5
0084R 41B0                BAL    15,STABS
          000F
0088R C510                CLHI   1,PI
          3258
008CR 4280                BL     COMPAR
          0098R
0090R C850                LHI    5,TWOPI
          64AE
0094R 0B51                SHR    5,1
0096R 0815                LHR    1,5
0098R C510      COMPAR    CLHI   1,X'600'          ^^20 DEGREES
          0600
009AR           MINIM     EQU    *-2
009CR 4280                BL     GOON
          00A8R
00A0R C810                LHI    1,-1
          FFFF
00A4R 4300                B      GOON+2
          00AAR
00A8R 0711      GOON      XHR    1,1
00AAR 4010                STH    1,SFLAG+2
          0158R
00AER 4010                STH    1,NOFIX+2
          010ER
00B2R 4810                LH     1,ESTORE
```

```
                000F
00B6R 4330              BZ      NOEX
                00CR
0008            DAT     EQU     8
00BAR C880              IHI     DAT,DAT
                000F
00BER 4838              LH      3,0(DAT)
                0000
00C2R C430              NHI     3,X'3FFF'
                3FFF
00C6R 4828              LH      2,2(DAT)
                0002
00CAR C420              NHI     2,X'3FFF'
                3FFF
00CER 0A32              AHR     3,2
00D0R CC30              SRHL    3,1             GET 'AVERAGE' I
                0001
00D4R 4848              LH      4,6(DAT)
                0006
00D8R C440              NHI     4,X'3FFF'
                3FFF
00DCR 4828              LH      2,8(DAT)
                0008
00E0R C420              NHI     2,X'3FFF'
                3FFF
00E4R 0A42              AHR     4,2
00E6R CC40              SRHL    4,1             GET 'AVERAGE' I
                0001
00EAR 0722              XHR     2,2
00ECR 4532      CLOOP   CLH     3,INDEX(2)
                000F
00F0R 4280              BL      HNEXT
                00FCR
00F4R 4020              STH     3,NOEX+2
                00CER
00F8R 4300              B       NEXT
                0104R
00FCR 4542      HNEXT   CLH     4,INDEX(2)
                00EER
0100R 4380              BNL     FOUND
                0124R
0104R 2622      NEXT    AIS     2,2
0106R 0521              CLHR    2,1
0108R 4280              BL      CLOOP
                00ECR
010CR C820      NOEX    LHI     2,0
                0000
0110R 2412              LIS     1,2
0112R 0A21              AHR     2,1
0114R 4841              LH      4,CORNER(1)
                000CR
0118R 4874              LH      7,STORE(4)
```

```
                0000
011CR 4834              LH      3,STORE2(4)
                0002
0120R 4300              B       SHIFT
                012CR
0124R 4872      FOUND   LH      7,STOREX(2)
                0000F
0128R 4832              LH      3,STOREY(2)
                0000F
012CR 0744      SHIFT   XHR     4,4
012ER 2452              LIS     5,2
0130R 4862      CLOOP1  LH      6,STOREX(2)
                0126R
0134R 4064              STH     6,STOREX(4)
                0132R
0138R 4862              LH      6,STOREY(2)
                012AR
013CR 4064              STH     6,STOREY(4)
                013AR
0140R 4862              LH      6,INDEX(2)
                00FER
0144R 4064              STH     6,INDEX(4)
                0142R
0148R 0A45              AHR     4,5
014AR 0A25              AHR     2,5
014CR 0521              CLHR    2,1
014ER 4280              BL      CLOOP1
                0130R
0152R 4040              STH     4,BSTORE
                00B4R
0156R C840      SFLAG   LHI     4,0
                0000
015AR 4210      BACK    BM      *
                015AR
015ER 4300              B       EXIT
                0000F


0162R 4030      ATNR    STH     ,DELTAX
                018CR
0166R 4040              STH     4,DELTAY
                018ER
016AR 41F0              BAL     15,ATANUR
                0000F
016ER 018CR             DC      DELTAX
0170R 018ER             DC      DELTAY
0172R 0190R             DC      ANGLE
0174R 4850              LH      5,ANGLE
                0190R
0178R 4860              LH      6,ANGLE+2
                0192R
017CR CF50              SLHA    5,12
```

```
          000C
  0130R CE60              SRHA   5,3
        0003
  0184R 0A56              AHR    5,6
  0186R 0300              BR     0

  0188R 0001    ONE       DC     1
  018AR 0002    TWO       DC     2
  018CR 0000    DELTAX    IC     0
  018ER 0000    DELTAY    DC     0
  0190R 0000    ANGLE     IC     0.0
        0000
  0194R                   END

NO ERRORS

  ANGLE    0190R
* ATANUR   016CR
  ATNR     0162R
  BACK     015AR
* BSTORE   0154R
* CFRTRN   0008R
* CFSA     0000R
  CLOOP    00ECR
  CLOOP1   0130R
  COMPAR   0098R
* CORNER   0116R
  CORNR    0008
  DAT      0008
* DATP     00BCR
  DELTAX   018CR
  DELTAY   018ER
  FOUND    0124R
  GOON     00A8R
  GOON1    0058R
  GOTAN    0060R
* GPOINT   0040R
  HNEXT    00FCR
* INDEX    0146R
* MINIM    009AR
  NEXT     0104R
  NOEX     010CR
  ONE      0188R
  PI       3258
* PTMAX    0044R
  SFLAG    0156R
  SHIFT    012CR
* STABS    0086R
  STORE    0000
  STORE2   0002
* STOREX   0136R
* STOREY   013ER
  TWO      018AR
```

```
  TWOPI    64AE
* XIT      0160F

*****************************************************************
```

```
*ENTRY BAL TO,CFIX
*      THIS ROUTINE TAKES 2 LINE SEGMENTS
*      IN 'CORNER' & CALCULATES THEIR INTERSEC
*      THE INTERSECTION IS STORED HIGH IN
*      STORE AND THE POINTERS TO THE INTERSECT
*      IN CORNER ARE ALTERED TO IT
*
*R0--BAL; B & D FROM BD
*R1--WRKG
*R2--WRKG,PTR TO CORNER IN SLOPED
*R3--B,D FROM BD; Y FROM BY,DY
*R4--WRKG
*R5--WRKG
*R6--WRKG; PTR TO HOLD IN SLOPED
*R7--WRKG
*R12-BAL SETTER
*R14-BAL SLOPED
*R15-BAL SLOPE1,STABS,BD,BY,DY



*   Y1=AX1+B
*   Y2=CX2+D
*      AT INTERSECTION:
*           Y1=Y2
*           X1=X2
*      THEREFORE: AX+B=CX+D AT INTERS
*   AX-CX=D-B
*   X(A-C)=D-B
*   X(INTERS)=(D-B)/(A-C)
*   Y(INTERS)=A*X(INTERS)+B=
*                C*X(INTERS)+D


0000R                  ENTRY CFIX,DELTA3,CRTRN,XIT
0000R                  EXTRN CORNCT,SLOPER
0000R                  EXTRN INOUTS
0000R                  EXTRN DATP,THOLD
0000R                  EXTRN CORNER,STABS
0000R                  EXTRN ATANUR

0000            STORE  EQU   0
0002            STORE2 EQU   2
000E            STOREE EQU   14
000C            STOREC EQU   12

0000R 4000      CFIX   STH   0,RETRN
      0238R
0004R 2442             LIS   4,2              SET PTR TO GET
0006R 41F0             BAL   15,BD            GET B
      0008ER
000AR 4000             STH   0,B
```

```
      030ER
000ER 2448          LIS   4,8             GET PTR TO GET
0010R 41F[          BA.   15,BD           GET D
      008ER
0014R 4000          STH   0,D
      0310R
0018R C900          CHI   0,X'9000'       IF D<900
      9000
001CR 4210          BM    DXY             LINE2 IS VERTIC
      00C6R
0020R C900          CHI   0,X'7000'       IF D>700
      7000
0024R 4220          BP    DXY             LINE2 IS VERTIC
      00C6R
0028R 4810          LH    1,B
      030ER
002CR C910          CHI   1,X'9000'       IF B<900
      9000
0030R 4210          BM    DXY             LINE1 IS VERTIC
      0164R
0034R C910          CHI   1,X'7000'       IF B>700
      7000
0038R 4220          BP    DXY             LINE1 IS VERTIC
      0164R
003CR 0B10          SHR   1,0             R1=B-D
003ER 424[          BIC   4,BOT           IF SLB. FAILS,S
      00DAR
0042R 4[10          MH    ),TANFAC        ADD IN ROUNDOFF
      031CR
0046R 244A          LIS   4,10
0048R 4854          LH    5,CORNER(4)     5 HAS C*TANFAC
      0000F
004CR 2746          SIS   4,6
004ER 4B54          SH    5,CORNER(4)     R5=(C-A)*TANFAC
      004AR
0052R 0820          LHR   2,0
0054R 0831          LHR   3,1
0056R 0D05          DHR   0,5             R1 HAS X AT COR
                *                   =(D-B)*TANF C/((A-C)*TANFA
0058R 0531          CLHR  3,1
005AR 4230          BNE   CHECK           CHECK FOR DIV F
      019AR
005ER 0520          CLHR  2,0
0060R 4230          BNE   CHECK           IF NONE GO TO C
      019AR
0064R 0811          LHR   1,1
0066R 4330          BZ    CHECK
      019AR
006AR C550          CLHI  5,1
      0001
006ER 4330          BE    CHECK
      019AR
```

```
0072R 4810            LH    1,B               OTHERWISE ONE L
      030ER
0076R 41B0            BAL   15,STABS          DECIDE WHICH
      0000F
007AR 0801            LHR   0,1
007CR 4810            LH    1,D
      0310R
0080R 41F0            BAL   15,STABS          AND GO TO APPRO
      0078R
0084R 0510            CLHR  1,0
0086R 4380            BNL   EXY
      00C6R
008AR 4300            B     DXY
      0164R


                *     ***************

                *
                *ENTRY BAL 15,BD
                *     THIS ROUTINE EXTRACTS B FROM THE
                *     EQUASION Y=AX+B
                *     B=Y-AX
                *
008ER 4814      BD    LH    1,CORNER(4)       R4=PTR TO 2ND L
      0050R
0092R 4831            LH    3,STORE(1)        R3=X
      0000
0096R 2642            AIS   4,2               R4 H.S  PTR TO
0098R 41C0            BAL   12,SETTER         IF RETURNED
      00A4R
                *                   R3 HAS AX
                *                   ELSE X INTERCEPT NEAR INFIN
009CR 4801            LH    0,STORE2(1)       R0 HAS Y
      0002
00A0R 0B03            SHR   0,3               R0=B
00A2R 03CF            BR    15



                *
                *ENTRY BAL 12,SETTER
                *     R3 HAS X ON ENTRY
                *     R4=PTR TO SLOPE OF LINE (A)
                *     R2/3 = AX ON EXIT
                *
00A4R 4C24      SETTER MH   2,CORNER(4)
      0090R
00A8R 0852            LHR   5,2
00AAR 0863            LHR   6,3
00ACR 4230            BNZ   HOP
      00B4R
```

```
00B0R 0822              LHR   2,2
00B2R 033C              BFCR  3,12
00B4R 4D20    HOP       DH    ,TANFAC          REMOVE ROUNDOFF
      031CR
00B8R 0536              CLHR  3,6
00BAR 023C              BTCR  3,12             CHECK FOR DIVID
00BCR 0525              CLHR  2,5              IF NONE RETURN
00BER 023C              BTCR  3,12
00C0R C800              LHI   0,X'8000'        ELSE LOAD R0=8=
      8000
00C4R 03)F              BR    15               RETURN TO CALLE
                *

                *       ********************

                * ENTRY E (B)XY
                *  BXY & DXY ARE IDENTICAL EXCEPT
                *  YOU USE BXY WHEN LINE2 IS VERTICAL
                *  USE DXY WHEN LINE1 IS VERTICAL.

                *WITH ONE LINE VERTICAL, X ALONG THAT
                *LINE WILL NOT CHANGE MUCH.  IF YOU
                *TAKE AN X NEAR THE INTERSECTION, IT CAN
                *BE SAFELY ASSUMED TO BE THE X AT THE
                *INTERSECTION.  SUBSTITUTING THIS X I.
                *THE EQUASION FOR THE OTHER LINE GIVES
                *Y( INTERS)

                *
00C6R 4810    BXY       LH    1,B
      030ER
00CAR C910              CHI   1,X'9000'        SEE IF BOTH LIN
      9000
00CER 4210              BM    BOTH
      00DAR
00D2R C910              CHI   1,X'7000'
      7000
00D6R 4320              BNP   NOT              IF NOT  GO TO N
      014AR
00DAR 48F0    BOTH      LH    15,RETRN         IF FROM INTERS
      0238R
00DER 480F              LH    0,0(15)
      0000
00E2R C500              CLHI  0,INOUTS
      0000F
00E6R 0330              BER   :                RETURN
00E8R 2442              LIS   4,2
00EAR 2438              LIS   3,8              ELSE YOU HAVE A
00ECR 0824              LHR   2,4
```

```
00EER 4813     LOOP    LH      1,CORNER(3)     FORGET IT &
      00A6R
00F2R 4014             STH     1,CORNER(4)     TO LOOK FOR NEX
      00F0R
00F6R 4813             LH      1,DATP(3)
      0000F
00FAR 4014             STH     1,DATP(4)
      00F8R
00FER 0A32             AHR     3,2
0100R 0A42             AHR     4,2
0102R C540             CLHI    4,8
      0008
0106R 4280             BL      LOOP
      00EER
010AR 484C             LH      4,CORNCT
      0000F
010ER 2746             SIS     4,6
0110R 4040             STH     4,CORNCT
      00CCR
0114R 41F0             BAL     15,SLOPER
      0000F
0118R C830             LHI     3,THOLD
      0000F
011CR 2634             AIS     3,4
011ER 4843             LH      4,STOREC(3)
      000C
0122R 4043             STH     4,STORE(3)
      0000
0126R 4843             LH      4,STOREE(3)
      000E
012AR 4043             STH     4,STORE2(3)
      0002
012ER 2638             AIS     3,8
0130R 4843             LH      4,STOREC(3)
      000C
0134R 4043             STH     4,STORE(3)
      0000
0138R 4843             LH      4,STOREE(3)
      000E
013CR 4043             STH     4,STORE2(3)
      0002
0140R 48F0             LH      15,RETRN
      0238R
0144R 480F             LH      0,0(15)
      0000
0148R 0300             BR      0
014AR 2446     NOT     LIS     4,6             GET END OF LINE
014CR 4824             LH      2,CORNER(4)     NEAREST INTERSE
      00F4R
0150R 4812             LH      1,STORE(2)      GET ITS X COORD
      0000
0154R 41F0             BAL     15,BY           CALCULATE Y
```

```
      017ER
0158R 4030            STH   3,Y1
      03AAR
015CR 4030            STH   3,Y2              STORE IT FOR L1
      030CR
0160R 4300            B     CHEKR             SKIP CALCULATIO
      01AAR


0164R 2442    DXY     LIS   4,2
0166R 4824            LH    2,CORNER(4)
      014ER
016AR 4812            LH    1,STORE(2)
      0000
016ER 41F0            BAL   15,DY
      018CR
0172R 4030            STH   3,Y1
      030AR
0176R 4030            STH   3,Y2
      030CR
017AR 4300            B     CHEKR
      01AAR


                *
                *ENTRY BAL 15,(B)Y
                *  BY & DY ARE IDENTICAL; THEY ARE
                *  USED TO CALCULATE Y WHEN X IS
                *  KNOWN.  BY IS USED FOR LINE1; DY
                *  FOR LINE2.
                *ON ENTRY, R1 HAS X-COORD AT THE
                *  INTERSECTION
                *ON RETURN, R3 HAS Y
                *
017ER 0831    BY      LHR   3,1
0180R 2444            LIS   4,4
0182R 41C0            BAL   12,SETTER         GET AX
      00A4R
0186R 4A30            AH    3,B               Y=AX+
      030ER
018AR 030F            BR    15


018CR 0831    DY      LHR   3,1
018ER 244A            LIS   4,10
0190R 41C0            BAL   12,SETTER
      00A4R
0194R 4A30            AH    3,I
      0310R
0198R 030F            BR    15
```

```
                *       ***************

                *
019AR 41F0      CHECK   BAL     15,BY           GET Y AT INTERS
      017ER
019ER 4030              STH     3,Y1            FOR LINE1
      030AR
01A2R 41F0              BAL     15,DY           GET INTERSECTIO
      018CR
01A6R 4030              STH     3,Y2            FOR LINE2
      030CR

                *       YOU'VE NOW GOT TWO POSSIBLE INTERSECTIO
                *       X,Y1 & X,Y2.  YOU WOULD LIKE TO FIND
                *       FIND THE ONE WHICH IS CLOSEST
                *       TO THE INTENDED CORNER
                *FIND THE LINE ALONG WHICH THE DIFFERENCE
                * IN LINE SLOPE

**********************************************************************

                * IS GREATER (BETWEEN X,Y1 & X,Y2)  THEN FIND
                * THE X,Y COORD WHICH GIVES THE LINE THE SLOP
                * CLOSER TO THE ONE ORIGINALLY CALCULATED
                *

01AAR 4010      CHEKR   STH     1,H1
      0218R
01AER 0B66              SHR     6,6
01B0R 0B22              SHR     2,2
01B2R 41F0              BAL     14,SLOPED       GET DIF BETWEEN
      023ER
                *                       FOR LINES X,Y1-CORNER(0
                *                         X,Y2-CORNER00)
01B6R 4010              STH     1,DEL1          STORE THE DIFFE
      031AR
01BAR 2426              LIS     2,6
01BCR 2464              LIS     6,4
01BER 41F0              BAL     14,SLOPED       SAME FOR CORNER
      023ER
01C2R 4510              CLH     1,DEL1          FIND WHICH LINE
      031AR
01C6R 4380              BNL     SCND
      01D8R
01CAR 0B66              SHR     6,6
01CCR 2422              LIS     2,2
01CER 4812              LH      1,CORNER(2)
      0168R
```

```
01D2R 0722            XHR   2,2
01D4R 4300            B     RET1
      01DER
01D8R 2426      SCND  LIS   2,6
01DAR 4812            LH    1,CORNER(2)
      01D0R
01DER 4851      RET1  LH    5,STORE2(1)
      0002
01E2R 4831            LH    3,STORE(1)
      0000
01E6R 41B0            BAL   15,DIFFER
      0288R
01EAR 4816            LH    1,HOLD(6)
      0312R
01EER 0B15            SHR   1,5             GET DIF BETW CA
                *               SLOPE FOR X,Y1 & SLOPE OF
                *               LINE SEGMENT NEAREST
01F0R 41D0            BAL   13,PITEST
      026AR
01F4R 4010            STH   1,DEL1
      031AR
01F8R 4816            LH    1,HOLD1(6)
      0314R
01FCR 0B15            SHR   1,5             SAME FOR X,Y2
01FER 41D0            BAL   13,PITEST
      026AR
0202R 4510            CLH   1,DEL1          FIND WHICH IS L
      031AR
0206R 4280            BL    SEC
      0212R
020AR 4830            LH    3,Y1            LOAD R3 WITH NE
      030AR
020ER 4300            B     RET2
      0216R
0212R 4830      SEC   LH    3,Y2
      030CR
0216R C870      RET2  LHI   7,0
      0000
0218R           HI    EQU   *-2
021AR 2416      XIT   LIS   1,6
021CR 4841            LH    4,CORNER(1)     GET POINTER TO
      01DCR
0220R 4074            STH   7,STORE(4)
      0000
0224R 4034            STH   3,STORE2(4)
      0002
0228R 2714            SIS   1,4
022AR 4841            LH    4,CORNER(1)
      021ER
022ER 4074            STH   7,STORE(4)
      0000
0232R 4034            STH   3,STORE2(4)
```

```
                0002
0236R C8[illegible]0                IHI   [illegible],0
                0000
0238R                   RETRN       EQU   *-2
0238R                   CFRTRN      EQU   *-2
023AR 26[illegible]2                AIS   [illegible],2
023CR 03D[illegible]                BR    [illegible]


                        *
                        *ENTRY BAL 14,SLOPED
                        *       R15--BAL
                        *       R14--RETURN ADDR
                        *       R2--CORNER PTR
                        *       R1--STABS(SLOPE DIF) ON RETURN
                        *       R6--PTR TO HOLD
                        *       R3,R5--WRKG

023ER 4850              SLOPED  LH    5,Y1
      030AR
0242R 4830                      LH    3,H1              H1 HAS X COORD
      0218R
0246R 41F0                      BAL   15,DIFFER
      0288R
024AR 4056                      STH   5,HOLD(6)         R5=SLOPE (X,Y1-
      0312R
024ER 4830                      LH    3,H1
      0218R
0252R 4850                      LH    5,Y2
      030CR
0256R 41F0                      BAL   15,DIFFER
      0288R
025AR 4056                      STH   5,HOLD1(6)        R5=SLOPE (X,Y2-
      0314R
025ER 4816                      LH    1,HOLD(6)
      0312R
0262R 0B15                      SHR   1,5
0264R 41D0                      BAL   13,PITEST
      026AR
0268R 030E              EXIT    BR    14


026AR 41F[illegible]    PITEST  BAL   15,STABS
      0082R
026ER C510                      CLHI  1,X'3257'
      3257
0270R                   PI      EQU   *-2
0272R 028D                      BTCR  8,13
0274R 4230                      BNE   NOTBAC
      027CR
```

```
0278R 0B11              SHR   1,1
027AR 030D              BR    13
027CR C820      NOTBAC  LHI   2,X'64AE'
      64AE
027ER           TWOPI   EQU   *-2
0280R 0B12              SHR   1,2
0282R 41B0              BAL   15,STABS
      026CR
0286R 030D              BR    13

0288R 40B0      DIFFER  STH   15,HOLDF
      0306R
028CR 4812              LH    1,CORNER(2)
      022CR
0290R 0875              LHR   7,5
0292R 0843              LHR   4,3
0294R 4B51              SH    5,STORE2(1)
      0002
0298R 4B31              SH    3,STORE(1)
      0000
029CR 2622              AIS   2,2
029ER 4812              LH    1,CORNER(2)
      028ER
02A2R 2722              SIS   2,2
02A4R 4B71              SH    7,STORE2(1)
      0002
02A8R 4B41              SH    4,STORE(1)
      0000
02ACR 0817              LHR   1,7
02AER 41F0              BAL   15,STABS
      0284R
02B2R 4010              STH   1,TEMPH
      02D6R
02B6R 0814              LHR   1,4
02B8R 41B0              BAL   15,STABS
      028CR
02BCR 61D0              AHM   1,TEMPH
      02D6R
02C0R 0815              LHR   1,5
02C2R 41F0              BAL   15,STABS
      02BAR
02C6R 4010              STH   1,TEMPH1
      02D2R
02CAR 0813              LHR   1,3
02CCR 41B0              BAL   15,STABS
      02C4R
02D0R CAD0              PHI   1,0
      0000
02D2R           TEMPH1  EQU   *-2
02D4R C510              CLHI  1,0
      0000
02D6R           TEMPH   EQU   *-2
```

```
02D8R 4380                BNL   OK
      02E0R
02DCR 1857                LHR   5,7
02DER 1834                LHR   3,4
02E0R 4030      OK        STH   3,DELTAX
      0320R
02E4R 4050                STH   5,DELTAY
      031ER
02E8R 41F0                BAL   15,ATANUR
      000OF
02ECR 031ER               DC    A(DELTAY),A(DELTAX),A(ANGLE)
      0320R
      0322R
02F2R 4850                LH    5,ANGLE
      0322R
02F6R 4830                LH    3,ANGLE2
      0324R
02FAR CF50                SLHA  5,12
      000C
02FER CE30                SRHA  3,3
      0003
0302R 0A53                AHR   5,3
0304R 4300                B     *
      0304R
0306R           HOLDF     EQU   *-2


0308R           DELTA3    DS    2
030AR           Y1        DS    2
030CR           Y2        DS    2
030ER           B         DS    2
0310R           D         DS    2
0312R           HOLD      DS    2
0314R           HOLD1     DS    2
0316R           HOLD2     DS    2
0318R           HOLD3     DS    2
031AR           DEL1      DS    2
031CR 0040      TANFAC    DC    X'40'
031ER           DELTAY    DS    2
0320R           DELTAX    DS    2
0322R           ANGLE     DS    2
0324R           ANGLE2    DS    2
0326R                     END
ANGLE    0322R
ANGLE2   0324R
* ATANUR  02EAR
B        030ER
BD       0008ER
BOTH     00DAR
EXY      00C6R
BY       017ER
* CFIX    0000R
```

```
* CFRTRN  0238R
  CHECK   019AR
  CHEKR   01AAR
* CORNCT  0112R
* CORNER  02A0R
  D       0310R
* DATP    00FCR
  DEL1    031AR
* DELTA3  0308R
  DELTAX  0320R
  DELTAY  031ER
  DIFFER  0288R
  DXY     0164R
  DY      018CR
  EXIT    0268R
  H1      0218R
  HOLD    0312R
  HOLD1   0314R
  HOLD2   0316R
  HOLD3   0318R
  HOLDF   0306R
  HOP     00B4R
* INOUTS  00E4R
  LOOP    00EER
  NOT     014AR
  NOTBAC  027CR
  OK      02E0R
  PI      0270R
  PITEST  026AR
  RET1    01DER
  RET2    0216R
  RETRN   0238R
  SCND    01D8R
  SEC     0212R
  SETTER  00A4R
  SLOPED  023ER
* SLOPER  0116R
* STABS   02CER
  STORE   0000
  STORE2  0002
  STOREC  000C
  STOREE  000E
  TANFAC  031CR
  TEMPH   02D6R
  TEMPH1  02D2R
* THOLD   011AR
  TWOPI   027ER
* XIT     021AR
  Y1      030AR
  Y2      030CR
```

```
0000R                    ENTRY DELT11,DELT22
0000R                    ENTRY LINER,DELTA1,DELTA2
0000R                    EXTRN CORNER,GPOINT
0000R                    EXTRN PRLOOP,WNWOVE
0000R                    EXTRN LADD,PPFIDF,FAID
0000R                    EXTRN DATP
0000R                    ENTRY FLINE,FLINE2
0000R                    EXTRN PTMAX

0000              STORE  EQU  0
0006              STORE6 EQU  6


                  *REGS: 0 RETURN,BAL
                  *      1
                  *      2 CONTAINS CORNCT
                  *      3
                  *      4
                  *      5
                  *      6 CONTAINS RMAX
                  *      7
                  *      8
                  *      9
                  *     10 PTR TO LINE END FROM PLOOP
                  *     12 MULTIPLY,DIVIDE--
                  *     13 DATA CHANGES
                  *     15 BAL
0000R 4000        LINER  STH  0,RETRN
      00C0R
0004R 4020             STH  2,HOLD
      00B8R
0008R 4090             STH  9,HOLD2
      00BCR
000CR 4060             STH  6,HRATE
      0148R
0010R 4810             LH   1,DELT11
      0140R
0014R 4010             STH  1,DELTA1
      013CR
0018R 4810             LH   1,DELT22
      0142R
001CR 4010             STH  1,DELTA2
      013ER
0020R 4812             LH   1,DATP(2)
      0000F
0024R 4210             BM   GETPT
      0030R
0028R 4810             LH   1,HOLDPT
      015ER
002CR 4012             STH  1,CORNER(2)
      0000F
0030R 41F0        GETPT  BAL  15,PLOOP2
```

```
                00CAR
0034R 40A0      0146R           STH     10,FLINE2
0038R 2622                      AIS     2,2
003AR 41F0      00CAR           BAL     15,PLOOP2
003ER 40A0      015ER           STH     1 ,HOLDPT
0042R 40A0      0144R           STH     10,FLINE
0046R 41F0      0000F           BAL     15,LADD
004AR 000A                      DC      10
004CR 0000F                     DC      PTMAX
004ER 0144R                     DC      FLINE
0050R 0146R                     DC      FLINE+2
0052R 014AR                     DC      SIZE
0054R 08EE                      LHR     14,14
0056R 4230      0000F           BNZ     PRLOOP
005AR 41F0      0000F           BAL     15,PPFLDF
005ER 000E                      DC      14
0060R 004CR                     DC      PTMAX
0062R 0144R                     DC      FLINE
0064R 0146R                     DC      FLINE+2
0066R 015CR                     DC      FIELD1
0068R 015AR                     DC      TWO
006AR 0148R                     DC      HRATE
006CR 08EE                      LHR     14,14
006ER 4230      0058R           BNZ     PRLOOP
0072R 41F0      0000F           BAL     15,GPOINT
0076R 000A                      DC      10
0078R 0060R                     DC      PTMAX
007AR 0144R                     DC      FLINE
007CR 0158R                     DC      ONE
007ER 00C2R                     DC      X1
0080R 41B0      0074R           BAL     15,GPOINT
0084R 000A                      DC      10
0086R 0078R                     DC      PTMAX
0088R 0144R                     DC      FLINE
008AR 015AR                     DC      TWO
008CR 00C4R                     DC      Y1
008ER 41F0      0082R           BAL     15,GPOINT
0092R 000A                      DC      10
0094R 0086R                     DC      PTMAX
0096R 0146R                     DC      FLINE+2
0098R 0158R                     DC      ONE
```

```
00C6R                  DC     X2
00CAR 41F0             BAL    15,GPOINT
      0090R
00D0R 0010             DC     10.
00D2R 0094R            DC     PTMAX
00D4R 0146R            DC     FLINE+2
00D6R 015AR            DC     TWO
00D8R 00C8R            DC     Y2
00DAR C890             LHI    9,X1
      00C2R
00DER C8C0             LHI    12,X2
      00C6R
00E2R 4D00             BAL    0,WNWONE
      0000F
00E6R C820 RETRY2      LHI    2,0
      0000
00E8R      HOLD        EQU    *-2
00EAR C890             LHI    9,HOLD2
      00ECR
00ECR      HOLD2       EQU    *-2
00EER 4300             B      *
      00EER
00F0R      RETRN       EQU    *-2
           *
00F2R      X1          DS     2
00F4R      Y1          DS     2
00F6R      X2          DS     2
00F8R      Y2          DS     2
           *

00FAR D000 PLOOP2      STM    12,SAV4
      0134R
00FER 4060             STH    6,SAV6+2
      0130R
0102R 48A2             LH     10,CORNER(2)
      002ER
0106R 4860             LH     6,PTMAX
      00A2R
010AR 45A6             CLH    10,6(6)
      0006
010ER 4280             BL     KNOWN
      012AR
0112R 4330             BE     KNOWN
      012AR
0116R 40A0             STH    10,X
      00F8R
011AR 26A2             AIS    10,2
011CR 40A0             STH    10,Y
      00FAR
0120R 41F0             BAL    15,PADD
      0000F
0124R 0008             DC     8
```

```
00F6R 00D8R            DC     PTMAX
00F8R 0000     X       DC     0
00FAR 0000     Y       DC     0
00FCR 08AE             LHR    10,14
00FER 40E0             STH    14,VPN
      0150R
0102R 41F0             BAL    15,LADD
      0048R
0106R 000A             DC     10
0108R 00F6R            DC     PTMAX
010AR 0150R            DC     VPN
010CR 014ER            DC     ZERO
010ER 0156R            DC     LSIZE
0110R 48D2             LH     13,DATP(2)
      0022R
0114R 40D0             STH    13,PLACE
      0152R
0118R 41B0             BAL    15,PPFLDF
      005CR
011CR 000E             DC     14
011ER 00D8R            DC     PTMAX
0120R 0150R            DC     VPN
0122R 014ER            DC     ZERO
0124R 0154R            DC     FIELD2
0126R 014CR            DC     FOUR
0128R 0152R            DC     PLACE
012AR D1C0     KNOWN   LM     12,SAV4
      0134R
012ER C860     SAV6    LHI    6,0
      0000
0132R 03DF             BR     15

                *
0134R          SAV4    DS     8
013CR          DELTA1  DS     2
013ER          DELTA2  DS     2
0140R          DELT11  DS     2
0142R          DELT22  DS     2
0144R          FLINE   DS     2
0146R          FLINE2  DS     2
0148R 0000     HRATE   DC     0
014AR 000C     SIZE    DC     12
014CR 0004     FOUR    DC     4
014ER 0000     ZERO    DC     0
0150R 0001     VPN     DC     1
0152R 0000     PLACE   DC     0
0154R 0009     FIELD2  DC     9
0156R 000C     LSIZE   DC     12
0158R 0001     ONE     DC     1
015AR 0002     TWO     DC     2
015CR 0007     FIELD1  DC     7
015ER 0000     HOLDPT  DC     0
```

```
 0160R                    END

NO ERRORS

* CORNER  00D4R
* DATP    0112R
* DELT11  0140R
* DELT22  0142R
* DELTA1  013CR
* DELTA2  013ER
  FIELD1  015CR
  FIELD2  0154R
* FLINE   0144R
* FLINE2  0146R
  FOUR    014CR
  GETPT   0030R
* GPOINT  009ER
  HOLD    00B8R
  HOLD2   00BCR
  HOLDPT  015ER
  HRATE   0148R
  KNOWN   012AR
* LADD    0104R
* LINER   0000R
  LSIZE   0156R
  ONE     0158R
* PADD    00F2R
  PLACE   0152R
  PLOOP2  00CAR
* PPFLDF  011AR
* PRLOOP  0070R
* PTMAX   011ER
  RETRN   00C0R
  RETRY2  00B6R
  SAV4    0134R
  SAV6    012ER
  SIZE    014AR
  STORE   0000
  STORE6  0006
  TWO     015AR
  VPN     0150R
* WNWONE  00B4R
  X       00F8R
  X1      00C2R
  X2      00C6R
  Y       00FAR
  Y1      00C4R
  Y2      00C8R
  ZERO    014ER
```

****

```
004CR 4280                BL    NEXT              PT IS EXTREME I
      00EAR
0050R 4570                CLH   7,GREAT1           4B6>+DIFF>0192
      013ER
0054R 4280                BL    EXTREM
      0070R
0058R 4300                B     NEXT              ELSE LOOK AT NE
      00EAR
005CR 4570    LOWLM       CLH   7,SMALL           PT IS EXTREME I
      013CR
0060R 4380                BNL   NEXT              FE6E>-DIFF>FB40
      00EAR
0064R 4570                CLH   7,SMALL1
      0140R
0068R 4380                BNL   EXTREM
      0070R
006CR 4300                B     NEXT              ELSE LOOK AT NE
      00EAR
0070R 48B0    EXTREM      LH    11,BSTORE
      0182R
0074R CBB0                SHI   11,2
      0002
0078R 4310                BNM   DTEST
      0084R
007CR CAB0                AHI   11,2
      0002
0080R 4300                B     GOES
      00E6R
0084R CAD0    DTEST       AHI   13,INCREM
      0006
0088R 48FD                LH    15,STORE(13)
      002AR
008CR 487D                LH    7,STORE2(13)
      0038R
0090R 4BFB                SH    15,STOREX(11)
      0154R
0094R 4B7B                SH    7,STOREY(11)
      0166R
0098R 0CEF                MHR   14,15
009AR 0C67                MHR   6,7
009CR CBD0                SHI   13,INCREM
      0006
00A0R CAB0                AHI   11,2
      0002
00A4R 0AF7                AHR   15,7
00A6R 0EE6                ACHR  14,6
00A8R 08EE                LHR   14,14
00AAR 423D                BNZ   GOES
      00B6R
00AER 45D0                CLH   15,MIN             SEE IF EXTREMES
      0138R
00B2R 4280                BL    NEXT
```

```
        00EAR

00B6R 4870      GOES    LH      7,DISKST
      0000F
00BAR CD70              SLHL    7,7
      0007
00BER 08FD              LHR     15,13
00C0R 4BF0              SH      15,OFFSET
      0000F
00C4R 067F              OHR     7,15
00C6R 407B              STH     7,INDEX(11)
      0142R
00CAR 48FD              LH      15,STORE(13)
      008AR
00CER 40FB              STH     15,STOREX(11)
      0154R
00D2R 48FD              LH      15,STORE2(13)
      008ER
00D6R 40FB              STH     15,STOREY(11)
      0166R
00DAR CAB0              AHI     11,2
      0002
00DER 40B0              STH     11,BSTORE
      0182R
00E2R 4050              STH     5,SLOP3
      0186R
00E6R 4300              B       INCR
      00F2R
00EAR 48F0      NEXT    LH      15,SLOP2
      0184R
00EER 40F0              STH     15,SLOP3
      0186R
00F2R 4050      INCR    STH     5,SLOP2
      0184R
00F6R           BACK    EQU     *
00F6R C850      SAV5    LHI     5,0
      0000
00FAR C860      SAV6    LHI     6,0
      0000
00FER C870      SAV7    LHI     7,0
      0000
0102R C8B0      SAV11   LHI     11,0
      0000
0106R C8D0      SAV13   LHI     13,0
      0000
010AR C8E0      SAV14   LHI     14,0
      0000
010ER 4300      SAV15   B       *
      010ER
```

```
0006            INCREM  EQU   6

0000R                   EXTRN STORE,STORE2,ATANUR
0000R                   ENTRY TAG
0000R                   ENTRY EXTRMR
0000R                   ENTRY BSTORE,SLOP2,SLOP3,GREAT,GREAT1
0000R                   ENTRY SMALL,SMALL1,TAN1,STOREX,STOREY
0000R                   ENTRY MIN,INDEX
0000R                   EXTRN STORE,STORE2
0000R                   EXTRN OFFSET,DISKST

                        *
                        * EXTRMR EXPECTS PTR TO CURRENT POINT IN R13
0000R 4050      EXTRMR  STH   5,SAV5+2
      00F8R
0004R 4060              STH   6,SAV6+2
      00FCR
0008R 4070              STH   7,SAV7+2
      0100R
000CR 40B0              STH   11,SAV11+2
      0104R
0010R 40D0              STH   13,SAV13+2
      0108R
0014R 40E0              STH   14,SAV14+2
      010CR
0018R 40F0              STH   15,SAV15+2
      0110R
001CR 485D              LH    5,STORE(13)       R5=X2
      0000F
0020R 486D              LH    6,STORE2(13)      R6=Y2
      0000F
0024R CBD0      GO      SHI   13,INCREM
      0006
0028R 487D              LH    7,STORE(13)
      001ER
002CR C570              CLHI  7,X'8000'
      8000
0030R 4330              BE    GO
      0024R
0034R 0B57              SHR   5,7               X2-X1
0036R 4B6D              SH    6,STORE2(13)      Y2-Y1
      0022R
003AR 41E0              BAL   14,TAN1           CALL ARCTAN SUB
      0112R
003ER 4870              LH    7,SLOP3
      0186R
0042R 0B75              SHR   7,5               BECAUSE RE=0 IN
0044R 4210              BM    LOWLM             -90<1ST SLOP<+9
      005CR
0048R 4570              CLH   7,GREAT           NOT STORED AS 1
      013AR
```

```
 0112R 4050      TAN1     STH    5,DX
       017AR
 0116R 4060               STH    5,DY
       0178R
 011AR 41F0               BAL    15,ATANUR          CALL FLOATING P
       000F
 011ER 0178R              DC     A(DY),A(DX),A(RESULT)
       017AR
       017CR
 0124R 4850               LH     5,RESULT           TO EXPRESS FLOA
       017CR
 0128R CF50               SLHA   5,8                IN ONE HALF WOR
       0008
 012CR 4860               LH     6,FRACTN
       017ER
 0130R CE60               SRHA   6,7                SO THAT THE 3RD
       0007
 0134R 0A56               AHR    5,6                IS 1ST SIGNIFIC
 0136R 03DE               BR     14
 0138R 0211      MIN      DC     X'211'
 013AR 0192      GREAT    DC     X'0192'            PI/2 OR 90 DEGR
 013CR FE6E      SMALL    DC     X'FE6E'            -PI/2 OR -90 DE
 013ER 04B6      GREAT1   DC     X'04B6'            3PI/2 OR 270 DE
 0140R FB40      SMALL1   DC     X'FB40'            -3PI/2 OR -270
 0142R           INDEX    DS     18
 0154R           STOREX   DS     18
 0166R           STOREY   DS     18
 0178R           DY       DS     2
 017AR           DX       DS     2
 017CR           RESULT   DS     2
 017ER           FRACTN   DS     2
 0180R           TAG      DS     2
 0182R           BSTORE   DS     2
 0184R           SLOP2    DS     2
 0186R           SLOP3    DS     2
 0188R                    END

NO ERRORS

* ATANUR   011CR
  BACK     00F6R
* BSTORE   0182R
* DISKST   00B8R
  DTEST    0084R
  DX       017AR
  DY       0178R
  EXTREM   0070R
* EXTRMR   0000R
  FRACTN   017ER
  GO       0024R
  GOES     00B6R
* GREAT    013AR
* GREAT1   013ER
```

```
  INCR     00F2R
  INCREM   0006
* INDEX    0142R
  LOWLM    005CR
* MIN      0138R
  NEXT     00EAR
* OFFSET   00C2R
  RESULT   017CR
  SAV11    0102R
  SAV13    0106R
  SAV14    010AR
  SAV15    010ER
  SAV5     00F6R
  SAV6     00FAR
  SAV7     00FER
* SLOP2    0184R
* SLOP3    0186R
* SMALL    013CR
* SMALL1   0140R
* STORE    00CCR
* STORE2   00D4R
* STOREX   0154R
* STOREY   0166R
* TAG      0180R
* TAN1     0112R

*****************************************************************
```